

Linear Vapor Tight LED



TYPICAL APPLICATIONS

- > Warehouses
- > Industrial Plants
- > Manufacturing Facilities
- > Work benches
- > Supermarkets




DESCRIPTION

Housed in a durable aluminum casing to deliver optimal heat dissipation. This Vapor Tight is an IP65 wet listed product, making it waterproof and dust-proof. It can be surface or suspended mounted, with customizable cord length, and optional integrated motion sensor.

FEATURES

- > Durable aluminum casing for optimal heat dissipation
- > Suspended or Surface mount the fixture
- > Includes 6' hardwired cord
- > Optional motion sensor
- > In-series transient voltage surge suppressor (TVSS)
- > UL1598 Listed
- > Warranty details can be found at www.tactiklighting.com



Linear Vapor Tight LED




SPECIFICATIONS

Power Factor.....>0.9
 Input Voltage120/277V
 Performance.....Up to 110 lm/W
 Operational Temperature.....-20°C to 55°C (-4°F to 131°F)
 Calculated Lifetime..... L₇₀ Lifetime per TM21 is 121,000 hours
 Color Rendering Index>80
 Distribution.....120°
 Mount Type.....Suspended or Surface Mounted
 Available Wattages.....24W, 30W, 40W, 50W, 60W
 Available Color Temperatures.....3000K, 4000K, 5000K
 Available Lengths.....2 ft, 4 ft

DISTRIBUTION

The light distribution curve shows you how the light will react within a space. In the chart below, the horizontal center line of the graph is the ceiling, and the colored charted lines are how the light will react from the ceiling to the floor for a certain distribution.



Maximum Candela = 1922.69 Located At Horizontal Angle = 90, Vertical Angle = 1
 # 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
 # 2 - Vertical Plane Through Horizontal Angles (0 - 180)

ORDERING INFORMATION

SAMPLE ORDER NUMBER: EPM-LL-VT-02-24-PF-30-PR-1-AA-MS

Manufacturer	Series	Type	Length	Wattage	Tube Opacity	Color Temp	Premium	Input Voltage	Color	Motion Sensor
EPM - ePOWER Manufacturing	LL - Linear LED	VT - Vapor Tight	02 - 2 Ft	24 - 24W 30 - 30W	PF - Frosted	30 - 3000K 40 - 4000K 50 - 5000K	PR - Premium	1 - 120/277V	AA - Anodized Aluminum WH - White	(blank) - No Motion Sensor MS - Motion Sensor
			04 - 4 Ft	40 - 40W 50 - 50W 60 - 60W						
EPM	LL	VT					PR	1		

*Fixture cord not included – see Cord Spec Sheet for ordering information.

ACCESSORIES

Installation Accessories	Part Number
Linear Vapor Tight Motion Sensor Remote	EPM-LL-VT-MS-R

LUMINOUS OUTPUT

Wattage	3000K	4000K	5000K
24W	2,482 lm	2,640 lm	2,640 lm
30W	2,919 lm	3,300 lm	3,300 lm
40W	4,088 lm	4,400 lm	4,400 lm
50W	5,259 lm	5,500 lm	5,500 lm
60W	6,185 lm	7,384 lm	7,615 lm