



TECHNICAL DATA SHEET

485 KENMORE BLVD.
AKRON, OH 44301-1013
WEB SITE: www.ruscoec.com

THE RUSCOE COMPANY
P.O. BOX 3858
AKRON, OH 44314-0858
E-MAIL: sales@ruscoe.com

PHONE: 330-253-8148
FAX: 330-253-2933
TOLL FREE: 800-293-8148

DH888 Flying Splice Adhesive

Ruscoec's DH888 is used as a newspaper roll splicing adhesive during printing. DH888 can also be used to temporarily position materials such as cloth, leather, and paper. DH888 has a brushable viscosity, fast drying solvent system, and red color for easy application.

PROPERTIES:

Solids	37-44%
Viscosity	3000-4000 cps (Brookfield #2 @ 4 rpm)
Color	Red
Density	6.5 #/gal (0.78 g/mL)
Solvents	Aliphatic Hydrocarbons

APPLICATION:

DH888 is typically brush or roller applied but can be sprayed with appropriate dilution. For spray application, dilute 1:1 with mineral spirits, textile spirits, VM&P naphtha, hexane, toluene, xylene or mixtures of these solvents.

Apply DH888 to either surface to be bonded. It is not necessary to coat both surfaces. Allow adhesive to become tacky dry. Assemble substrates and apply adequate pressure to ensure full contact.

CLEANING:

DH888 can be cleaned using mineral spirits, textile spirits, VM&P naphtha, hexane, toluene, or xylene.

STORAGE:

DH888 is flammable and should be stored below 100°F (37.7°C) in tightly sealed containers away from direct sunlight, heat, sparks, or other potential sources of ignition. Shelf life is 24 months from date of manufacture when stored appropriately. See Safety Data Sheet for more information on storage and disposal.

All statements, technical information and recommendations contained herein are based on tests believed to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties expressed or implied.

Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before using, user shall determine the suitability of the product for their intended use and user assumes all risk and liability whatsoever in connection therewith.

The foregoing may not be changed except by an agreement signed by officers of seller or manufacturer. January 2018