


**Proven Professionally  
...Everyday**



*High Tack*  
**MASTIC  
ADHESIVE**

**No 383**

This quick tack construction grade adhesive will bond many special building and construction materials including: DuPont Tyvek® Housewrap and polyethylene film to wood, steel, aluminum and concrete, or to one another. May be repositioned.

Open time exceeds 30 minutes, with a wide temperature application range from 20°F. to +100°F. Will also adhere to wet or frozen lumber!

*Approved by E.I. DuPont  
for use on Tyvek® Housewrap,  
Bonds Quickly,  
May be Repositioned.*

Apply 1/4" mastic bead to bonding area — then press adherends firmly together. If mastic bead surface skins over before bonding is achieved, be sure to press firmly to break skin so wet adhesive can coat second surface properly.  
**DO NOT APPLY DIRECTLY TO POLYSTYRENE FOAM.**

Tyvek® Spunbonded olefin—Trademark of E.I. DuPont Company.

**This pressure-sensitive mastic adhesive is specially designed to bond polyethylene film during construction of wood foundations and reduces staple holes in film or DuPont Tyvek® Housewrap.**

This heavy mastic adhesive is a rubber-resin formulation in a special solvent formulation. High Tack mastic adhesive is pressure sensitive so that it has instant grab on practically all surfaces used in construction.

High Tack mastic may be applied by cartridge dispenser to a clean, dry surface; no thinning is required. Drying time is approximately 5 minutes for a surface skin but adhesive bead remains tacky for about 14 days permitting easy repositioning as it will re-bond to itself.

Full cure 14 days— For cleanup use petroleum distillates.



**RUSCOE**  
CONSTRUCTION GRADE  
ADHESIVES

**NOTICE TO CUSTOMER**

Because we do not know the particular use for which this product may be purchased nor how it may be applied, we cannot guarantee its suitability for your purpose. However, we will refund the purchase price if this product is defective. This shall be the customer's only remedy. We cannot assume any obligation or liability for the results of customer use or a customer's inability to use this product. Test before use.

© W.J. RUSCOE COMPANY 2000



**W. J. RUSCOE COMPANY**

485 Kenmore Blvd. Akron, Ohio 44301-1013  
330-253-8148 • FAX 330-253-2933 • 800-293-8148  
Web-Site: [www.ruscoec.com](http://www.ruscoec.com) E-Mail: [sales@ruscoec.com](mailto:sales@ruscoec.com)