


MC700 Pluggable PCB Connector, Plug



DIMENSIONS/POSITIONS

MC700-500..A

MC700-500..B

間距	Pitch	5.00mm	5.00mm
位數	Poles	2 ~ 22Poles	2 ~ 22Poles
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
導電夾片	Contact	Phosphor Bronze, Tin Plated	Phosphor Bronze, Tin Plated
電線線徑	Wire Size	12 ~ 28AWG	12 ~ 28AWG
剝線長度	Wire Strip Length	8mm ~ 9mm	8mm ~ 9mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流 I _n Nominal Current I _n	16A	16A
額定橫截面 Nominal Cross Section	1.5mm ²	1.5mm ²
最大負載電流 Maximum load current	16A	16A
絕緣材料 Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94	V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL	300V	300V
額定電流,UL/CUL Nominal current, UL/CUL	16A	16A

