




# Fiber Optic Cable

## Furcation Tubing

2.0mm Breakout Tubing, PVDF Inner



### Part Number:

**C200157-XXX**

Replace XXX with:

- BLU - BLUE
- ORG - ORANGE
- GRN - GREEN
- BRN - BROWN
- GRY - GREY
- WHT - WHITE
- RED - RED
- BLK - BLACK
- YEL - YELLOW
- VIO - VIOLET
- PNK - PINK
- AQU - AQUA



### Mechanical

**Diameter:** 0.079" (2.0mm) Tolerance +/- 0.003/ .08mm

**Tensile Load:**

Installation: 50 lbs (220N) Max.

Operating: 15 lbs (66N) Max

**Minimum Bend Radius:**

Installation: 1.58" (4.01cm)

Operating: 0.79" (2.0 cm)

**Cable Weight:** 1.7 lbs/1000ft (2.54kg/km)

**Operating Temperature:** -4F to 167F (-20C to 75C)

**Storage Temperature:** -40F to 167F (-40C to 75C)

### Construction:

**Inner Tube:**

Diameter: 0.020" x 0.035" (.5mm x .9mm) +/- 0.002" (0.05mm)

Tubing Color: natural

**Strength Member:**

Dielectric Aramid Yarn Fibers

**Outer Jacket:**

Jacket Color: blue, orange, green, brown, slate, white  
red, black, yellow, violet, pink, aqua

Material: Flame Retardant PVC

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Opticonx, Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Opticonx, Inc. IS PROHIBITED.

**Applications Note:**

This tubing is designed for upjacketing 250um fiber to 2mm for direct termination.

Drawn By: PS  
Approved By: PL  
Date: 06/16/15  
Rev: A