

128 Grades and grade requirements for the class Blackeye Beans.

| Grade | Percent Maximum Limits of --- | | | | | | |
|--|-------------------------------|--|------------------|--------------------------------|--------|-------------------------------------|---------------------------------------|
| | Moisture ¹ | Total Defects (Total damaged, Total foreign material, Contrasting classes, & Splits) | Total Damaged | Foreign Material | | Contrasting Classes ² | Classes that Blend ³ |
| | | | | Total (including stones) | Stones | | |
| U.S. No. 1 | 18.0 | 4.0 | 2.0 | 0.5 | 0.2 | 0.5 | 5.0 |
| U.S. No.2 | 18.0 | 6.0 | 4.0 | 1.0 | 0.4 | 1.0 | 10.0 |
| U.S. No. 3 | 18.0 | 8.0 | 6.0 | 1.5 | 0.6 | 2.0 | 15.0 |
| <p>U.S. Substandard shall be beans which do not meet the requirements for the grades U.S. No. 1 through U.S. Sample grade. Beans which are not well screened shall also be U.S. Substandard, except for beans which meet the requirements for U.S. Sample grade.</p> <p>U.S. Sample grade shall be beans which are musty, sour, heating, materially weathered, or weevily; which have any commercially objectionable odor; which contain insect webbing or filth, animal filth, any unknown foreign substance, broken glass, or metal fragments; or which are otherwise of distinctly low quality.</p> <p>¹Beans with more than 18.0 percent moisture are graded High moisture. ²Beans with more than 2.0 percent contrasting classes are graded Mixed beans. ³Beans with more than 15.0 percent classes that blend are graded Mixed beans. [47 FR 19311, May 5, 1982] [47 FR 20547, May 13, 1982] [60 FR 36030, July 13, 1995] [62 FR 52967, Oct. 10, 1997] [69 FR 75504, Dec. 17, 2004]</p> | | | | | | | |