

**MUNICIPAL ACCESS PERMIT APPLICATION
(CURB & GUTTER SECTION)**

Name of Property Owner _____

Address _____

_____ Phone No. _____

Proposed Access Point:

Located on _____, also known as _____,
(Co. Rd. or CSAH No.) (Street Name)
accessing into Lot _____ of Block _____,
(Number) (Number) (Name)
Subdivision in the City of _____, on the _____ side of
(Name) (Direction)
the street.

For: Residential _____ (Check One)
Small Parcel _____
Business _____
Industrial _____

Attach a sketch on 8 1/2" x 11" paper showing the site with dimensions of opening and dimensions to nearest street intersection.

The Policy of Redwood County concerning municipal access approaches to Redwood County Roads is on the reverse side of this application form.

I hereby certify that I have reviewed the above policy and shall comply with it.

Date Signature of Applicant

Permission is hereby granted to construct this approach as herein specified and agreed upon by the application, provided the applicant has also received the approval of the City prior to any work being allowed.

Date County Engineer

Orig: Applicant
Copies: RCHD Maint. Supv.
File

Redwood County Highway Department
635 W. Bridge St., PO Box 6
Redwood Falls, MN 56283
Phone: 507-637-4056 Fax: 507-637-4068

Redwood County Policy

1. A written application for an access approach (entrance) permit shall be processed through the County Highway Engineer's office for each entrance requested.
2. All work is subject to the approval of the County Engineer.
3. The applicant shall be responsible for the construction & the materials needed to construct the entrance. All costs related to the entrance construction will be the applicant's expense. A \$1500 Deposit (either money order or certified check) will be required before approval of the application. The Deposit will be returned to the applicant upon final inspection and approval by the Highway Department.
4. All gravel base removed must be replaced and thoroughly recompact, with a final thickness equal to original, or greater.
5. All bituminous surfacing removed must be squared off, tack applied to all joints, and replaced with equal, or greater thickness of Mn/DOT bituminous mixture, type specified by the County Engineer.
6. Curb and Gutter removal and replacement is to be per the sketch below. Dowel all new-old joints.