



Project: _____
 Location: _____
 Cat. #: _____
 Type: _____
 Quantity: _____

LED

LEX | LED Exit Sign

Features:

- Ultra-bright, long life Red or Green LED
- Dual 120/277V
- 4.8V long life, maintenance free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Easy snap-out chevron directional indicators
- Dual-circuit option on the AC-only unit enables it to be connected to two different supplies at the same time, one acting as a back-up to the other
- Custom signs available with custom wording



Applications:

For use in dry or damp locations where exit signage is needed.

Ambient operating Temp.:

0°C to 50°C

Construction:

- Injection molded 5VA flame retardant, high-impact resistant thermoplastic housing

Mounting:

- Easy snap mounting canopy included for top or end mount
- Universal K/O pattern on back plate for wall mount

Certifications:

- UL listed for damp locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes



Warranty:

- 5 year limited warranty on housing and electronics. Battery pro rated for 5 yrs.
- see www.LumenFocus.com for complete warranty terms and conditions



Ordering Guide:

example: LEX 2 R DV W-EM SD US

Series	# of Faces	Letter Color	Voltage	Housing Color	Battery	Options
LEX LED Exit	2 Universal Single/ Double Face	R Red G Green	DV Dual 120/277V	W White B Black	Blank AC Only EM Battery Backup	Blank None SD Self Diagnostics (EM units only) 2C Dual Circuit (AC units only) US Assembled in the USA Custom() Custom Wording (specify wording)

Electrical Chart:

Catalog #	Input Watts (W)	Input Watts (W)	Input Amps (A)	Input Amps (A)
	120V	277V	120V	277V
LEX-RED/GREEN/EM/SD/2C	3.8	3.8	0.034	0.020

Schematic:

