



RMTUHS31MGBGO

FEATURES

- * Rapid Deployment, Minimal Setup
- * No Earth Penetrations Required
- * Guyed to Outriggers / Trailer

SPECIFICATIONS

| | | |
|-------------------------------------|-------|---------------|
| EXTENDED HEIGHT : | | 31' |
| MINIMUM HEIGHT : | | 10' 10" |
| TOWER SECTIONS : | | 5 |
| MAXIMUM PAYLOAD : | | 400 LBS |
| TWIST : | | * |
| SWAY : | | * |
| DEFLECTION : | | * |
| TRANSPORT HEIGHT : | | 6' 10" (82") |
| TRANSPORT WIDTH : | | 8' (96") |
| TRANSPORT LENGTH : | | 13' 5" (161") |
| TRANSPORTABLE WEIGHT : | | 4,520 LBS |
| TONGUE WEIGHT : | | 620 LBS |
| DECK HEIGHT : | | 24" |
| NUMBER OF AXLES : | | 1 |
| C-130 TRANSPORTABLE : | | YES |
| ERECTABLE WIND SPEED : | | 35 MPH |
| MAXIMUM SAIL AREA : | | 9 SQ FT |
| TIME TO ELEVATE MAST/TOWER : | | 2 MINS |
| TIME TO LOWER MAST/TOWER : | | 2 MINS |
| TIME TO TILT/RAISE MAST/TOWER : | | 1 ½ MINS |
| DEPLOYMENT TIME (PERSONS/MINUTES) : | | 2 / 20 MINS |
| DEPLOYED FOOTPRINT : | | 32' X 26' 6" |
| TILT MECHANISM : | | HAND WINCH |

* To Be Determined : Twist, Sway and Deflection may vary depending on the type of payload.

NOTE: All values shown are approximate. Sensors shown in photo are optional equipment.