



Eaton 5PX UPS

Enterprise class battery backup with extended runtime designed for virtualized environments

5PX features and benefits:

Extended Runtime: Add up to four extended battery modules for maximum runtime.

Virtualization-ready: Available in convenient bundles with a network card and management software for rapid integration into your virtual environment.

Efficiency: Provides industry leading efficiency of up to 99 percent.

Manageability:

- **Energy metering:** The 5PX meters energy consumption right down to the outlet segments. No other UPS in the industry offers this capability.
- **UPS management:** By integrating the Eaton Intelligent Power[®] Manager software, you can monitor and manage the power devices on your network.

LCD display: Eaton's next generation LCD offers a graphical interface which provides all critical UPS information in a single screen view.

More power: Protects more devices by providing 28 percent more wattage compared to traditional UPSs.

Battery life: Eaton's exclusive ABM[®] technology increases battery service life by 50 percent.

Intelligent Power Manager (IPM)

By integrating IPM with the Eaton 5PX, you can:

- Remotely monitor and manage multiple devices across your network from a single interface; this can be integrated into an already existing platform, such as VMware, Microsoft or Citrix
- Suspend non-critical virtual machines, consolidate critical virtual machines and shut down unused servers to extend battery runtime.
- Set server power consumption limits for extended battery runtime with UCS management software

To learn more, please visit:

Eaton.com/intelligentpower

Services and support

Eaton provides product support 24 hours a day, 7 days a week. From battery replacement to full UPS service plans, Eaton has one of the top service models in the industry.

Three-year warranty

The 5PX warranty covers both the UPS and the batteries for three years.



Powering Business Worldwide

5PX MODEL SELECTION GUIDE*

| Catalog Number | Rating (VA / watts) | Input connection | Output receptacles | Dimensions (H x W x D), in | Net weight, lb |
|---|---------------------|------------------------------|-----------------------|-----------------------------------|-----------------------|
| 120V, 50/60 Hz | | | | | |
| 5PX1000RT | 1000 / 1000 | 5-15P | (8) 5-15R | 3.4 x 17.4 x 20.6 | 62 |
| 5PX1500RT | 1440 / 1440 | | | | 65 |
| 5PX2200RT | 1950 / 1920 | 5-20P | (8) 5-20R | 3.4 x 17.4 x 25.4 | 65 |
| 5PX3000RT2U | 3000 / 2700 | L5-30P | (1) L5-30R | | 87 |
| 5PX3000RT3U | | | (6) 5-20R | 86 | |
| 208V/230V, 50/60 Hz | | | | | |
| 5PX1500iRT | 1500 / 1350 | C14-10A | (8) C13-10A | 3.4 x 17.4 x 20.6 | 61 |
| 5PX2200iRT | 2200 / 1980 | C20-16A | (1) C19-16A | | 63 |
| 5PX3000iRT2U | 3000 / 2700 | | (8) C13-10A | 3.4 x 17.4 x 25.4 | 84 |
| 120V, 50/60 Hz Virtualization-ready bundles with Network Card-MS | | | | | |
| 5PX1500RTN | 1440 / 1440 | 5-15P | (8) 5-15R | 3.4 x 17.4 x 20.6 | 65 |
| 5PX2200RTN | 1950 / 1920 | 5-20P | (8) 5-20R | 3.4 x 17.4 x 20.6 | 65 |
| 5PX3000RTN | 3000 / 2700 | L5-30P | (6) 5-20R, (1) L5-30R | 3.4 x 17.4 x 25.4 | 87 |
| 208/230V, 50/60 Hz Virtualization-ready bundles with Network Card-MS | | | | | |
| 5PX3000iRTN | 3000 / 2700 | C20 | (8) C13, (1) C19 | 3.4 x 17.4 x 25.4 | 84 |
| Extended Battery Modules | | | | | |
| | DC voltage | For use with | Max qty / UPS | Dimensions (H x W x D), in | Net weight, lb |
| 5PXEBM48RT | 48V | All 1000, 1500 & 2200 models | 4 | 3.4 x 17.4 x 20.6 | 72 |
| 5PXEBM72RT2U | 72V | All 3000 2U models | | 3.4 x 17.4 x 25.4 | 102 |
| 5PXEBM72RT3U | | All 3000 3U models | | 5.1 x 17.4 x 19.6 | 98 |

*Due to continuous product improvement programs, all specifications are subject to change without notice. Please visit Eaton.com/5PX to view complete and updated product specifications.


| Additional Options | Catalog Number | For use with |
|---|------------------|---------------------------------------|
| Connectivity | | |
| Network Card-MS | NETWORK-MS | All models* |
| Environmental Monitoring Probe | 116750224-001 | All models (requires Network Card-MS) |
| Power Distribution & Bypass | | |
| HotSwap Maintenance Bypass (MBP) | EHBPL1500R-PDU1U | All 1000 & 1500 models |
| The HotSwap Maintenance Bypass allows you to exchange or service the UPS without shutting down the connected load | EHBPL2000R-PDU1U | All 2200 models |
| | EHBPL3000R-PDU1U | All 3000 models |
| Mounting Hardware | | |
| 2-post rail kit | 103007018-5591 | All models |

* Network Card-MS is included with catalog numbers 5PX1500RTN, 5PX2200RTN, 5PX3000RTN and 5PX3000iRTN.

What's in the box

- Tower pedestals
- Four-post rail kit
- User manual CD
- Quick start guide
- USB cable
- RS-232 serial cable
- Phillips Head screw driver
- 2 IEC to IEC jumper cables (208V/230V models)

5PX UPS rear panel (1000 & 1500 VA)



Battery runtime

You can get up to five hours of battery runtime using the internal batteries and extended battery modules. For a detailed, interactive battery runtime chart, please visit: Eaton.com/5PX (View the individual technical pages for details of each UPS.)



To interact with the Eaton 5PX, please visit: Eaton.com/5PX



Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com
Eaton.com/powerquality

© 2019 Eaton
All Rights Reserved
Printed in USA
5PX01FXA / GG
January 2019

Eaton, Intelligent Power and ABM are registered trademarks.
All other trademarks are property of their respective owners.