

TECHNICAL DATA



GREASE-OUT LOW FOAMING LAUNDRY DETERGENT

Product Description and Purpose

GREASE-OUT is generally used at a dilution rate of 1 to 4 ounces per gallon. **GREASE-OUT** is designed to be used in conjunction with **GRIME-AWAY**.

Features/Benefits

Economical

Concentrated

Surfaces Applicable

All washable fabrics.

General Usage Directions

Grease-Out may be used to launder shrouds, aprons, uniforms or other fabrics used in the plant. Rinse thoroughly with clean water to remove traces of wash detergent.

Physical Properties

Boiling Point:	212°F
Specific Gravity:	1.0
Vapor Pressure:	N/A
% Volatile:	69.1%
Vapor Density (Air = 1):	N/A
Evaporation Rate (Water = 1):	Initially 1
Solubility in Water:	Complete in all proportions
Appearance and odor:	Clear yellow liquid with citrus fragrance

Caution

Keep out of the reach of children. Harmful if swallowed. Avoid contact with skin, eyes and mucous membranes. Wear rubber gloves, goggles, and protective clothing when handling product or use solution.



1204 SW Jefferson Street
Lee's Summit, MO 64081
816-524-1304
Fax: 816-524-3260
www.ckinc.com