

## SC1305-1C L2 5-ports CCTV Din-Rail Hardened Unmanaged GE Ethernet Switch

5-ports Switch 4 - ports 10/100/1000BASE-T (RJ-45) and one Combo Gigabit ports each comprised of a RJ-45 and a SFP for uplink with DC:12/24/36/48V for extreme temperatures operation -30 to 70°C.



### Product Description:

The OPTICAL SNS SC1305-1C is Part of the successful DaVinci family of hardened Din-Rail CCTV and Industrial POE Ethernet Switches. The DaVinci SX1213 is a line of high-class rugged switches that provide high availability and designed for hard environments to enhance the operation of the network. The DaVinci SX1213 Series of Switches enhances any network performance by providing 10/100/1000 Mbps communication over existing Category 5/6 copper cabling as well as High Speed fiber-optic connectivity to the backbone through Small Form-Factor Pluggable (SFP) optical transceivers. The DaVinci SX1213 Series Switches are in a compact size Din-Rail form factor, it is ideal for robust outdoor application like video surveillance / FTTx and Wi-Fi coverage in critical environments. The switches provide a rich and versatile selection of Gigabit and Fast Ethernet port density. The DaVinci SX1213 Series provide a rugged enclosure designed to support high level EMC capability. The compact size, the Din-Rail form factor and the space-saving provide unique solution for installers and easy deployment.

The SC1305-1C CCTV Hardened Din-Rail Unmanaged GE Ethernet Switch 4 - ports 10/100/1000BASE-T (RJ-45) and one Combo Gigabit ports each comprised of a RJ-45 and a SFP for uplink with DC:12/24/36/48V for extreme temperatures operation -30 to 70°C .



## **Ease of Use**

The OPTICAL SNS SC1305-1C is truly a Plug-&-Play switch. The switch operates straight out of the box, with no configuration required. Auto MDI/MDIX ports identify and adapt to the Ethernet cable type, eliminating the most common cabling errors and simplifying installation. The SC1305-1C includes many useful features listed below:

### **Auto Speed Sensing.**

The Switch senses whether a network device is running at 10Mbps, 100Mbps or 1000Mbps and automatically adjusts for optimal performance.

### **Auto Negotiation (Full or Half Duplex).**

Whether you are running at Half- or in Full-Duplex, the Switch automatically negotiates and runs the highest supported transmission rate.

### **Auto MDI/MDIX Crossover.**

All ports support auto-negotiating MDI/MDIX detection, which eliminates the need for crossover cables or uplink ports. The SC1305-1C is the perfect choice for Plug-&-Play support for 10BASE-T and 100BASE-T networks.

### **Wire-speed Performance**

The SC1305-1C features a non-blocking wire-speed architecture, with a 10 Gbps switching capacity, for maximum data throughput. The OPTICAL SNS SC1305-1C also features an integrated per port diagnostics LEDs that make it easy to “spot check” for problems. With wire-speed filtering and Store-and-Forward switching, the SC1305-1C maximizes network performance while minimizing the propagation of bad network packets.

### **Exceptional Value**

Each SC1305-1C is backed by a limited 5-year warranty on the electronics (3 year limited warranty for fans/power supplies) by combining ease of use, unsurpassed 10/100BASE-T switching performance, and world-class support, the SC1305-1C raises the price-performance bar for unmanaged Layer 2 switching.

## Features and Benefits

<b>L2 Features</b>	
<b>MAC Table</b>	<b>8K</b>
<b>Packet Buffer</b>	<b>1M</b>
<b>Switching Capacity</b>	<b>10Gbps</b>
<b>Switching Delay</b>	<b>&lt;4us</b>
<b>Power</b>	<b>Power Input: 12-36VDC</b>
	<b>Overload Protection: Support</b>
<b>Environmental Limits</b>	<b>Operating/Storage Temperature: -30 to 70°C (-22 to 158°F)</b>
	<b>Ambient Relative Humidity: 5 to 95% (non-condensing)</b>
<b>MTBF</b>	<b>357,000 HRs</b>
<b>Warranty</b>	<b>5 years</b>
<b>Approvals</b>	<b>CE, FCC</b>
<b>Industrial Level Protection</b>	<b>ESD: ±8kV</b>
	<b>Level 3 EMC</b>
<b>Physical</b>	<b>Housing: Metal, Fanless</b>
<b>Dimensions (WxHxD) mm</b>	<b>137*25*88</b>
<b>Weight</b>	<b>0.35kg</b>



## Members of the DaVinci SX1213 family are:

### SC1213 Series:

- **SC1205:** Hardened Din-Rail CCTV Unmanaged FE Ethernet Switch 5 - ports 10/100BASE-T (RJ-45) with DC:12/24/36/48V for extreme temperatures operation -30 to 70°C
- **SC1208:** Hardened Din-Rail CCTV Unmanaged FE Ethernet Switch 8 - ports 10/100BASE-T (RJ-45) with DC:12/24/36/48V for extreme temperatures operation -30 to 70°C
- **SC1305:** Hardened Din-Rail CCTV Unmanaged GE Ethernet Switch 5 - ports 10/100/1000BASE-T (RJ-45) with DC:12/24/36/48V for extreme temperatures operation -30 to 70°C
- **SC1305-1C:** Hardened Din-Rail CCTV Unmanaged GE Ethernet Switch 4 - ports 10/100/1000BASE-T (RJ-45) and one Combo Gigabit ports each comprised of a RJ-45 and a SFP for uplink with DC:12/24/36/48V for extreme temperatures operation -30 to 70°C
- **SC1310-2C:** Hardened Din-Rail CCTV Unmanaged GE Ethernet Switch 8 - ports 10/100/1000BASE-T (RJ-45) and two Combo Gigabit ports each comprised of a RJ-45 and a SFP for uplink with DC:12/24/36/48V for extreme temperatures operation -30 to 70°C

### SCP1213 Series:

- **SCP1205:** Hardened Din-Rail CCTV Unmanaged FE Ethernet Switch 4 - ports 10/100BASE-T (RJ-45) PoE (802.3af/at) and one 10/100Base-T ports with DC:48V for extreme temperatures operation -30 to 70°C
- **SCP1210-1C:** Hardened Din-Rail CCTV Unmanaged FE Ethernet Switch 8 - ports 10/100BASE-T (RJ-45) PoE (802.3af/at) and one Gigabit port SFP for uplink with DC:48V for extreme temperatures operation -30 to 70°C
- **SCP1305:** Hardened Din-Rail CCTV Unmanaged GE Ethernet Switch 4 - ports 10/100/1000BASE-T (RJ-45) PoE (802.3af/at), one 10/100/1000Base-T ports for uplink with DC:48V for extreme temperatures operation -30 to 70°C
- **SCP1305-1C:** Hardened Din-Rail CCTV Unmanaged GE Ethernet Switch 4 - ports 10/100/1000BASE-T (RJ-45) PoE (802.3af/at) and one Combo Gigabit ports each comprised of a RJ-45 and a SFP uplink with DC:48V for extreme temperatures operation -30 to 70°C
- **SCP1310-2C:** Hardened Din-Rail CCTV Unmanaged GE Ethernet Switch 8 - ports 10/100/1000BASE-T (RJ-45) PoE (802.3af/at) and two Combo Gigabit ports each comprised of a RJ-45 and a SFP uplink with DC:48V for extreme temperatures operation -30 to 70°C

### SII1213 Series

- **SII1205:** Hardened Din-Rail industrial Unmanaged FE Ethernet Switch 5-ports 10/100BASE-T (RJ-45) with DC:12/24/36/48V for extreme temperatures operation -40 to 85°C
- **SII1208:** Hardened Din-Rail industrial Unmanaged FE Ethernet Switch 8 - ports 10/100BASE-T (RJ-45) with DC:12/24/36/48V for extreme temperatures operation -40 to 85°C
- **SII1303-1X:** Hardened Din-Rail industrial Unmanaged GE Ethernet Switch 2 - ports 10/100/1000BASE-T (RJ-45) and one 1000Base-X ports for uplink with DC:12/24/36/48V for extreme temperatures operation -40 to 85°C
- **SII1305:** Hardened Din-Rail industrial Unmanaged GE Ethernet Switch 5 - ports 10/100/1000BASE-T (RJ-45) with DC:12/24/36/48V for extreme temperatures operation -40 to 85°C
- **SII1305-1C:** Hardened Din-Rail industrial Unmanaged GE Ethernet Switch 4 - ports 10/100/1000BASE-T (RJ-45) and one Combo Gigabit ports each comprised of a RJ-45 and a SFP for uplink with DC:12/24/36/48V for extreme temperatures operation -40 to 85°C

### SIP1213 Series

- **SIP1205:** Hardened Din-Rail industrial Unmanaged FE Ethernet Switch 4 - ports 10/100BASE-T (RJ-45) PoE (802.3af/at) and one 10/100BASE-T (RJ-45) ports for uplink with DC:12/24/36/48V for extreme temperatures operation -40 to 85°C
- **SIP1210-1C:** Hardened Din-Rail industrial Unmanaged FE Ethernet Switch 8 - ports 10/100BASE-T (RJ-45) PoE (802.3af/at), one 10/100/1000BASE-T (RJ-45) port and one Gigabit port SFP for uplink with DC:48V for extreme temperatures operation -40 to 85°C
- **SIP1305-T:** Hardened Din-Rail industrial Unmanaged GE Ethernet Switch 4 - ports 10/100/1000BASE-T (RJ-45) PoE (802.3af/at) and one 10/100/1000BASE-T for uplink with DC:48V for extreme temperatures operation -40 to 85°C
- **SIP1305-T:** Hardened Din-Rail industrial Unmanaged GE Ethernet Switch 4 - ports 10/100/1000BASE-T (RJ-45) PoE (802.3af/at) and one Combo Gigabit ports each comprised of a RJ-45 and a SFP uplink with DC:48V for extreme temperatures operation -40 to 85°C

#### Ordering Information

**SC1305-1C**      **Hardened Hardened Din-Rail CCTV Unmanaged GE Ethernet Switch 4 - ports 10/100/1000BASE-T (RJ-45) and one Combo Gigabit ports each comprised of a RJ-45 and a SFP for uplink with DC:12/24/36/48V for extreme temperatures operation -30 to 70°C**

#### Gigabit Ethernet SFP

**SNS SFP-G-SX**      **SFP 1000Base-SX, MM, 850nm, 0-550m.**

**SNS SFP-G-MMX**      **SFP 1000Base-SX, Extended MM, 1310nm, 0-2km.**

**SNS SFP-G-LX**      **SFP 1000Base-LX, SM, 1310nm, 10km.**

**SNS SFP-GD-ELX**      **SFP 1000Base-ELX, SM, 1310nm, 25km**

**SNS SFP-GD-XD**      **SFP 1000Base-XD, SM, 1550nm, 50km**

**SNS SFP-GD-ZX**      **SFP 1000Base-ZX, SM, 1550nm, 80km**

**SNS SFP-GD-EZX**      **SFP 1000Base-EZX, SM 1550nm, 120km**

**For further information please visit us at - <http://opticalsns.com>**