

## OfficeSmart® Daily Planner Series

## Level 1 Antistatic Carpet Tile

### PHYSICAL PROPERTIES

<b>Construction</b>	Tufted
<b>Texture</b>	Multi-Level Pattern Loop
<b>Gauge</b>	1/12
<b>Density</b>	5,035
<b>Recycled Content</b>	40.4%
<b>Stitches per Inch</b>	8.5
<b>Average Pile Height</b>	0.114 inch (2.9 mm)
<b>Fiber</b>	Premium Branded ECO Solution Q Nylon
<b>Dye Method</b>	100% Solution Dyed
<b>Conductive Fiber Technology</b>	Continuous Conductive StaticSmart Monofilament
<b>Tufted Yarn Weight</b>	16 oz. per sq. yd. (542.49 g/m <sup>2</sup> )
<b>Standard Size</b>	24" x 24" (60.9 cm x 60.9 cm)
<b>Installation Method</b>	



### ANTISTATIC CONTROL PROPERTIES

<b>Electrostatic Propensity</b>	<b>AATCC 134-06</b> Less than 2.0 kV (2,000 volts)
---------------------------------	--

<b>Primary Backing System</b>	Non-Woven Synthetic
<b>Secondary Backing System</b>	EcoWorx® Backing: 100% PVC-Free, Phthalate-Free, Recyclable and made from Recycled Material
<b>Protective Treatments</b>	ssp® Shaw Soil Protection
<b>Indoor Air Quality</b>	Green Label Plus Certification
<b>Cradle to Cradle Certification™</b>	Silver Level
<b>Flammability</b>	<b>ASTM E-648</b> Flooring Radiant Panel - Class 1
<b>Smoke Density</b>	<b>ASTM E-662 NBS</b> Less than 450
<b>TARR</b>	Heavy Duty: >3.0
<small>(Texture &amp; Appearance Retention Rating)</small>	
<b>Warranty</b>	Lifetime Static Protection Lifetime Limited Commercial Warranty
<b>Availability</b>	No Minimums
<b>Packaging</b>	12 tiles per carton / 5.33 sq. yd.