



2021 5800lb Pro Stock 2wd Truck Rules

1. Any single 4-barrel carburetor. No cut or stretched carburetors. No tunnel ram or sheet metal intakes. No plates between the base and main body of carburetor.
2. OEM cylinder heads and blocks only. No racing, bowtie, or 502 blocks of any kind allowed. No aluminum block or heads. Factory serial # and casting # must be intact. OEM replacement cylinder heads allowed. No 934 GM Heads allowed. May remove material from head but cannot add to heads. No raised runners allowed (welding up or epoxy). Heads must retain stock valve angle.
 - a. 470 cubic inch max. 1% tolerance allowed.
 - b. Any cam ok.
 - c. No NOS or alcohol fuel (racing fuel ok)
 - d. Headers must go up or back No straight down or out headers allowed
 - e. Engie must be naturally aspirated. No blowers or turbo allowed.
3. Any battery-powered ignition may be used. No ignition that alters timing while running or in motion allowed
4. Bed may be hulled but not narrowed and must be covered. Rear bedside can be cut a maximum of 4" for tire clearance.
5. No cutting or gutting inside cab for weight advantages. Any pieces that can be unbolted may be removed. Allowed to remove dash. Factory firewall and floorboard required.
6. Front inner fenders not required. Must have shields 1 inch above spark plugs.
7. 133-inch wheel base maximum. If bed alterations are made, they must be from front of rear wheel well.
8. Frame must be no less than 1/2ton and not more than 1 ton. Frame may be cut to maintain maximum wheelbase. Brake caliper and brackets may be cut off. Rotors may be removed. No springs required. Radiator must be under hood in front of engine. One radiator per truck and must be in working order. Water holding tanks allowed but must be under hood in engine compartment. Straight axles are allowed. 133" wheelbase maximum. Allowed to use military frames. No shop built or home built frames allowed, must be OEM frame. Can brace factory frame.
9. If original vehicle has doors and hood, they must remain in place. Tilt front ends allowed. Windshields and back window required.
10. Tailgates and rear bumpers may be removed for safety of person hooking sled. Front OEM bumper is required per year model and body style. Bumpers must be same as make of truck.

11. Gas tanks cannot be mounted in front of truck. Fuel tank or cell must be inside bed of truck. Battery may be anywhere on truck except inside of cab or outside of bed.
12. Street legal tires only. No bar or tractor tires allowed. 12.50x17 street limit. No cut tires. Tire height limit 36 inches (by what is on tire). Wheel width limit 12 inches. Can be trued. Can run equivalent to 315-75-17 tire (metric size)
 - a. No dual wheels allowed
 - b. Tractor tires allowed on front
13. Front weights must be behind front bumper in stock position. Can be under hood in engine compartment. Rear weights cannot extend more than one (1) foot rear most part of the bed. Hitch support may be no farther back than hooking point.
14. Forty-two (42) inches minimum from center of rear axle to hitch point.
 - a. Hitch minimum 3 A inches long with 3-inch hole across. Hitch cannot go further forward than back of cab. No part of the hitch may exceed 3" to top. Top stop bracket not part of hitch.
15. Cool cans, electric fuel pump and fans allowed.
16. Maximum hitch height is 30" before, during and after the pull
17. No auxiliary box or transfer case allowed
18. Big rear-ends allowed. No planetary axles. Two speed factory stock allowed. Rear end cannot be any narrower than 62" (wheel flange to wheel flange). No sheet metal housings allowed.
19. Five speed or smaller transmissions allowed. No cut gears. Transmission must roll out per factory specifications or may pull cap. Stall converters allowed.
20. No more than double disc clutches allowed. Must be a pedal clutch. Must hold its own weight in 1st gear on an incline. No fully centrifugal clutches allowed. No glider clutches.
21. Full Size OEM truck bodies only. Fiberglass hoods are allowed.
22. Steering wheel and driver must remain within 3 inches of original position.
23. No individual brakes.
24. All general and safety rules not specified in rules will apply
25. It takes 100% to unlock the class rules. Majority to make any rule changes in class.
26. Class rules are locked until the end of 2024