

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

1 Identification

- **Product Identifier**
- **Trade Name: PAINT GUARD™ W/CARNAUBA WAX**
- **Product Number: K-331G**
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description: Hydrophobic Surface Enhance**
- **Application of the substance / the mixture: Automotive Clear-Coat Protectant**
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Kaady Chemical Corp.
2118 Adams St.
San Leandro, CA 94577
+1-510-562-9785
www.kaadychemical.com
- **Emergency telephone number: +1-800-424-9300**

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Acute Tox. 4 H302 Harmful if swallowed.
 Acute Tox. 4 H312 Harmful in contact with skin.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements:**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



- **Signal word: Warning**
- **Hazard-determining components of labeling:**
2-butoxyethanol
Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides
- **Hazard statements:**
H302+H312 Harmful if swallowed or in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements:**
P210 Keep away from heat. - No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing dust.

(Contd. on page 2)

US

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.
- P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice.
- P322 Specific measures (see supplementary first aid instructions on this Safety Data Sheet).
- P332+P313 If skin irritation occurs: Get medical advice.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing.
- P363 Wash contaminated clothing before reuse.
- P370+P380 In case of fire: Evacuate area.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.
0 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Non-hazardous components:

Non-Hazardous Components >60%

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

· Dangerous Components:

CAS: 111-76-2 RTECS: KJ 8575000	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Flam. Liq. 4, H227	<15%
CAS: 68155-39-5	Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated ⚠ Skin Irrit. 2, H315; Eye Irrit. 2B, H320	<10%
CAS: 61789-77-3	Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides ⚠ Acute Tox. 3, H301	<10%
CAS: 67-63-0 RTECS: NT 8050000	Isopropyl alcohol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	<5%

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

· Description of first aid measures:

· General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

· After inhalation:

Give oxygen or artificial respiration if needed. If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

· After skin contact:

Promptly flush skin with water for at least 15 minutes to ensure all chemical is removed. Remove contaminated clothing and wash before reuse. If reddening develops and/or persists, see a physician

· After eye contact:

Flush with large amounts of water for at least 15 minutes, lifting upper and lower lids occasionally. Remove contact lenses if present and easy to do so. Do not use chemical antidote. Get immediate medical attention

· After swallowing:

Rinse mouth with water. Give 3-4 glasses of water or milk to dilute stomach contents. Do NOT induce vomiting. Seek immediate medical attention.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed:

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

· Extinguishing media:

· Suitable extinguishing agents:

CO2, sand, dry chemical, water mist or alcohol resistant foam.

Use fire fighting measures that suit the environment.

· For safety reasons unsuitable extinguishing agents: No further relevant information.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

Special hazards arising from the substance or mixture:

- Carbon oxides
- Nitrogen oxides (NOx)
- Silicon oxides
- Aldehydes
- Organic Amines
- Hydrogen Chloride
- Methyl Chloride

Advice for firefighters:

Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

- Use personal protective equipment.
- Keep from contacting skin or eyes.
- Avoid breathing vapors, mist or gas.
- Ensure adequate ventilation.
- Evacuate personnel to safe areas.
- Remove all sources of ignition.

Environmental precautions: Do not allow to enter sewers/surface or ground water.

Methods and material for containment and cleaning up:

- Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.
- Dispose of the collected material according to regulations.

Reference to other sections:

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

111-76-2	2-butoxyethanol	60 ppm
67-63-0	Isopropyl alcohol	400 ppm

PAC-2:

111-76-2	2-butoxyethanol	120 ppm
67-63-0	Isopropyl alcohol	2000* ppm

PAC-3:

111-76-2	2-butoxyethanol	700 ppm
67-63-0	Isopropyl alcohol	12000** ppm

US

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
 Avoid breathing vapors or mist.
 Avoid contact with eyes, skin, or clothing.
 Use approved, plastic containers only - do not store in Aluminum.
 Keep containers closed when not in use.
 Do not expose containers to open flame, excessive heat, or direct sunlight.
 Do not puncture or drop containers.
 Handle with care and avoid spillage on the floor (slippage).
 Keep material out of reach of children.
 Keep material away from incompatible materials.
 Wash thoroughly after handling.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities:**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:**
 Store away from open flame, excessive heat, sparks or direct sunlight.
 Keep containers tightly closed.
 Store away from strong oxidizers.
 Store away from strong acids.
 Store away from strong bases.
 Store in plastic containers only.
 Store away from reactive metals (Zinc and Aluminum).
 Store away from acid anhydrides.
 Store away from halogenated compounds.
- **Further information about storage conditions:** None.
- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

67-63-0 Isopropyl alcohol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine urine end of shift Butoxyacetic acid with hydrolysis
-----	---

67-63-0 Isopropyl alcohol

BEI	40 mg/L urine end of shift at end of workweek Acetone (background, nonspecific)
-----	--

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Breathing equipment:**
Have self-contained breathing apparatus, positive pressure, MSHA/NIOSH (approved or equivalent) available in case of spillage or equipment failure.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Select glove material based on penetration times, rates of diffusion and degradation.

- **Material of gloves:**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.
Neoprene, Nitrile or Buna Rubber.
- **Penetration time of glove material:**
The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

 · **Eye protection:**


Safety glasses

9 Physical and Chemical Properties

 · **Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

Form:

Liquid

Color:

Clear amber

 · **Odour:**

Glycol-Ether Like

 · **Odor threshold:**

Not determined.

 · **pH-value @ 20 °C (68 °F):**

6-8

 · **Change in condition**

Melting point/Melting range:

Not determined.

Boiling point/Boiling range:

100 °C (212 °F)

 · **Flash point:**

None

 · **Flammability (solid, gaseous):**

Not applicable.

 · **Ignition temperature:**

Not applicable

 · **Decomposition temperature:**

Not determined.

 · **Danger of explosion:**

Product does not present an explosion hazard.

 · **Explosion limits:**

Lower:

Not determined.

Upper:

Not determined.

 · **Vapor pressure:**

Not determined.

 · **Density @ 20 °C (68 °F):**

 0.9710 g/cm³ (8.103 lbs/gal)

 · **Relative density:**

Not determined.

 · **Vapor density @ 20 °C (68 °F):**

 3.66 g/cm³ (30.543 lbs/gal)

 · **Evaporation rate:**

Not determined.

 · **Solubility in / Miscibility with:**

Water:

Fully Soluble

 · **Partition coefficient (n-octanol/water):** Not determined.

 · **Viscosity:**

Dynamic:

Not determined.

Kinematic:

Not determined.

 · **Solvent content:**

Organic solvents:

<20.0 %

(Contd. on page 8)

US

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

VOC content:	129 g/L
Solids content:	0.0 %
Other information:	No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Product is stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Incompatibilities, flames, ignition sources.
- **Incompatible materials:**
Peroxides, Nitric Acid, Reactive Metals (Zinc or Aluminum), Strong Acids, Strong Oxidizing Agents, Acid Anhydrides, Halogenated Compounds, Anionic Detergents
- **Hazardous decomposition products:**
Carbon Oxides, Nitrogen Oxides (NOx), Silicon Oxides, Aldehydes, Organic Amines, Hydrogen Chloride, Methyl Chloride.

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

111-76-2 2-butoxyethanol

Oral	LD50	470 mg/kg (Rat)
Dermal	LD50	220 mg/kg (rab)
Inhalative	LC50/4 h	2,174.91 mg/l (Rat)

67-63-0 Isopropyl alcohol

Oral	LD50	5,045 mg/kg (Rat)
Dermal	LD50	12,800 mg/kg (Rabbit)
Inhalative	LC50/4 h	30 mg/l (Rat)
	LC50/96 hours	9,640 mg/l (Pimephales)

- **Primary irritant effect:**
- **On the skin:** No irritating effect.
- **On the eye:** Irritating effect.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

Group 2B - Possibly carcinogenic to humans
 Group 3 - Not classifiable as to its carcinogenicity to humans
 Group 4 - Probably not carcinogenic to humans

111-76-2	2-butoxyethanol	3
67-63-0	Isopropyl alcohol	3

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

12 Ecological Information

· **Toxicity:**

· **Aquatic toxicity:**

111-76-2 2-butoxyethanol

EC50 1,815 mg/l (Water flea)

67-63-0 Isopropyl alcohol

EC50 6,851 mg/l (Green algae)

5,102 mg/l (Water flea)

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· **Results of PBT and vPvB assessment:**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

· **Waste treatment methods:**

· **Recommendation:**

Observe all federal, state and local environmental regulations when disposing of this material.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** *Non-Regulated Material*
- **UN proper shipping name:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** *Non-Regulated Material*
- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** *Non-Regulated Material*
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** *Non-Regulated Material*
- **Environmental hazards:** *Not applicable.*
- **Special precautions for user:** *Not applicable.*
- **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** *Not applicable.*
- **UN "Model Regulation":** *Non-Regulated Material*

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

- **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- **Section 313 (Specific toxic chemical listings):**

111-76-2 *2-butoxyethanol*

67-63-0 *Isopropyl alcohol*

- **TSCA (Toxic Substances Control Act):**

111-76-2 *2-butoxyethanol*

68155-39-5 *Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated*

61789-77-3 *Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides*

67-63-0 *Isopropyl alcohol*

- **TSCA new (21st Century Act) (Substances not listed)**

68155-39-5 *Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated*

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

· **California Proposition 65:**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **New Jersey Right-to-Know List:**

111-76-2 2-butoxyethanol

67-63-0 Isopropyl alcohol

· **New Jersey Special Hazardous Substance List:**

111-76-2 2-butoxyethanol

CA, F2

67-63-0 Isopropyl alcohol

F3

· **Pennsylvania Right-to-Know List:**

111-76-2 2-butoxyethanol

67-63-0 Isopropyl alcohol

· **Pennsylvania Special Hazardous Substance List:**

67-63-0 Isopropyl alcohol

E

· **Carcinogenic categories:**

· **EPA (Environmental Protection Agency):**

111-76-2 2-butoxyethanol

NL

· **TLV (Threshold Limit Value established by ACGIH):**

111-76-2 2-butoxyethanol

A3

67-63-0 Isopropyl alcohol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS07

· **Signal word:** Warning

· **Hazard-determining components of labeling:**

2-butoxyethanol

Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides

(Contd. on page 12)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX**· Hazard statements:***H302+H312 Harmful if swallowed or in contact with skin.**H315 Causes skin irritation.**H319 Causes serious eye irritation.***· Precautionary statements:***P210 Keep away from heat. - No smoking.**P233 Keep container tightly closed.**P261 Avoid breathing dust.**P264 Wash thoroughly after handling.**P270 Do not eat, drink or smoke when using this product.**P271 Use only outdoors or in a well-ventilated area.**P273 Avoid release to the environment.**P280 Wear protective gloves / eye protection / face protection.**P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.**P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.**P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.**P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P308+P313 IF exposed or concerned: Get medical advice.**P322 Specific measures (see supplementary first aid instructions on this Safety Data Sheet).**P332+P313 If skin irritation occurs: Get medical advice.**P337+P313 If eye irritation persists: Get medical advice/attention.**P362 Take off contaminated clothing.**P363 Wash contaminated clothing before reuse.**P370+P380 In case of fire: Evacuate area.**P403+P235 Store in a well-ventilated place. Keep cool.**P405 Store locked up.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***· National regulations:***None of the ingredients are listed.***· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other Information**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 04/14/2018 / 34**· Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 13)

US

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/14/2018

Reviewed on 04/14/2018

Trade Name: PAINT GUARD™ W/CARNAUBA WAX

DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety and Health
OSHA: Occupational Safety & Health Administration
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEL: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106