

# SANDUSKY SPEEDWAY

## 2020-2023 PURE STOCK RULES

IMPORTANT NOTICE: THE FOLLOWING SPECIFICATION HAVE BEEN PREPARED BY THE SANDUSKY SPEEDWAY OFFICIALS FOR THE CONSTRUCTION OF SANDUSKY SPEEDWAY PURE STOCK CARS. NO EXPRESS OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATIONS OF OR COMPLIANCE WITH RULES. THEY ARE INTENDED AS A GUIDE AND ARE IN NO WAY A GUARANTEE AGAINST INJURY OR DEATH TO PARTICIPANTS, SPECTATORS OR OTHERS.

NO EQUIPMENT WILL BE CONSIDERED AS HAVING BEEN APPROVED BY REASON OF HAVING PASSED THROUGH INSPECTION UNOBSERVED. ANYTHING NOT COVERED BY THESE GUIDELINES SHOULD BE APPROVED BY THE EVENT DIRECTOR OR CHIEF TECH INSPECTOR AND BE PLACED IN WRITING. TECH INSPECTOR WILL HAVE THE FINAL DECISION.

NOTICE: THESE RULES HAVE BEEN DEVELOPED FOR THE FUN OF RACING IN A LOW COST FASHION. THIS REQUIRES LIMITS IN VARIOUS AREAS TO KEEP COMPETITION EQUAL AND FAIR FOR ALL PARTICIPANTS. IN ORDER TO ACCOMPLISH THIS IF IT DOESN'T SAY YOU CAN – DON'T. WITH THE HELP AND CONSIDERATION OF THE PARTICIPANTS, THIS CAN BE ACCOMPLISHED. TRY TO LIVE WITHIN THE SPIRIT OF THE RULES. IF YOU HAVE QUESTIONS, PLEASE CONTACT BEAVER AT 567-219-1234 BETWEEN 5:30 AND 9 PM. CALLS ONLY NO TEXTS.

ANY CAR DEEMED TO BE UNSAFE BY TRACK OFFICIALS WILL NOT BE ALLOWED TO COMPETE

### 1. CAR BODY AND FRAME

- A. AMERICAN PASSENGER CAR WITH 108-INCH WHEEL BASE MINIMUM, FULL FRAME AND MUST BE LEFT STOCK. NO UNIBODYS
- B. CARS MUST HAVE FULL FLOORS, REAR AND FRONT FIREWALL, FLOOR MAY BE DECKED TO TOP OF THE HUMP.
- C. NO JEEPS, STATION WAGONS, CONVERTIBLES, VANS, FOUR WHEEL DRIVE CARS, OR FRONT WHEEL DRIVE CARS. ANY BODY STYLE MAY BE MOUNTED TO ANY CHASSIS (STEEL ONLY). FORD / CHRYSLER / MERCURY / ETC, BODIES ON GM METRIC CHASSIS (VICE / VERSA). FRAME & CHASSIS, ENGINE, TRANSMISSION AND REAR END MUST BE OF THE SAME MANUFACTURER.
- D. NO MODIFICATIONS TO FRAME WHATSOEVER. NO COMBINING /INTERCHANGING OF THE FRAME COMPONENTS. WHEEL BASE MUST BE WITHIN 1" OF ORIGINAL MANUFACTURE SPECIFICATIONS.
- E. FRAME HEIGHT MINIMUM 6".
- F. NO HOME MADE BODIES. MAXIMUM 6" SPOILER. NOT TO EXCEED THE WIDTH OF THE TOP OF THE QUARTERS. LEXAN WINDSHIELD AND REAR WINDOW PERMITTED. NO WINDOW DEFLECTORS.
- G. HOODS MUST HAVE 4 HOOD PINS AND 4 PINS IN TRUNK LID.
- H. BUMPERS MUST HAVE A CHAIN ON BOTH FRONT AND REAR.
- I. NO MIRRORS OF ANY KIND
- J. ROOF HEIGHT, NO LOWER THAN 51"
- K. FIBER GLASS BODIES MUST WEIGH 3350 LB.

L. ONLY MID 80'S FORD CROWN VIC FRAME CAN BE CUT TO 108 WHEEL BASE. MUST RUN STOCK REAR END TO THAT FRAME NO 9"

## 2. SUSPENSION

A. LOWER AND UPPER REAR CONTROL ARMS MUST BE STOCK LENGTH TO FRAME AND IN STOCK LOCATON. NO AFTER MARKET BUSHING MAY BE USED RUBBER ONLY.

B. AFTER MARKET SPRINGS MAY BE USED.

C. NO LOAD BOLTS. CAN HAVE ADJUSTABLE SPRING BUCKETS.

D. MUST RUN STOCK SPINDELS TO FRAME. STOCK BALL JOINTS ONLY. STOCK SWAY BAR NOT TO EXCEED 1 ¼" STOCK LINKS ONLY NO ADJUSTABLE SWAY BARS. STOCK MOUNTED SHOCKS, MONROE SHOCKS ONLY NO RACING SHOCKS GM: SH81494, 94001 5840 SH81492 and 5802 - Ford: SH81446, 94002, 5801, 5818 and 343135 Ford Crown Vic: SH81446, 94002. NO FORD 9" REAR ENDS OR REAR DISC BRAKES, STOCK BREAKS NO RACING BREAKS. NO DROP SPINDELS. 2 PIECE AFTER MARKET HUB AND ROTOR ALLOWED, MINIMUM 9/16 WHEEL STUDS, NO STEERING QUICKENERS, STEERING BOX IN STOCK LOCATION.

E. NO TRACTION CONTROL DEVICES OF ANY KIND

F. TUBULAR UPPER CONTROL ARM ARE ALLOWED 8" OR 8 ½" ONLY. LOWER CONTROL ARM MUST BE STOCK

G. NO ALUMINUM DRIVE SHAFTS

H. METRIC FRAMES 7.5 REAR END, CHEVELE 8.5 REAR END.

## 3. TRANSMISSIONS

A. ANY STOCK PRODUCTION AUTOMATIC TRANSMISSION ALLOWED.

B. STOCK O.E.M. TORQUE CONVERTER WITH O.E.M. STALL SPEED. NO DUMMY CONVERTERS C. ANY STOCK PRODUCTION 3 OR 4 SPEED ALLOWED. NO CENTER DROP OUTS

D. 360 DEGREE STEEL BLOW PROOF HOUSING IS MANDATORY FOR MANUALS.

E. NO ALUMINUM BELL HOUSING

F. A TRANSMISSION BLANKET OR STEEL TRANSMISSION FLOOR PAN IS HIGHLY RECOMMENDED FOR AUTOMATIC

G. NO RACING CLUTCHES

## 4. WHEELS AND TIRES

A. MAXIMUM 8" STEEL WHEEL

B. TIRE MUST BE AMERICAN RACER 970

C. WHEELS MUST FIT WITHIN WHEEL WELLS

D. NO AIR BLEEDER VALVES IN WHEELS

## 5. WEIGHT

A. MINIMUM 3300 LBS WITH DRIVER AFTER RACE

B. MAXIMUM 54% LEFT SIDE WEIGHT WITH DRIVER

C. MINIMUM OF 51% FRONT END WEIGHT WITH DRIVER

## 6. RADIATOR

- A. ANY RADIATOR STOCK LOCATION
- B. 180 DEGREE FAN SHROUD OR ELECTRIC FAN
- C. NO ANTI FREEZE OR ADDITIVES. IF FOUND WILL BE \$100 FINE

## 7. BATTERIES, ALTERNATOR AND IGNITION

- A. CAN NOT BE MOUNTED IN TRUNK
- B. STOCK HEI DISTRIBUTORS, NO DUAL POINT DISTRIBUTORS, NO SPARK BOXES, NO OUTSIDE COILS
- C. NO MARINE DISTRIBUTORS

## 8. GAS TANK

- A. FUEL CELLS MANDATORY. FUEL CELL MUST BE MOUNTED IN TRUNK AND SECURED TO FRAME BY AT LEAST 2 – 1" STEEL STRAPS NO LOWER THAN CENTER SECTION OF REAR END.
- B. RACING FUEL MAY BE USED. NO ALCOHOL, NO ADDITIVES.
- C. MUST HAVE A ROLL OVER VALVE

## 9. CARBURETOR

- A. STOCK OUT OF THE BOX 4412 HOLLYS, CHOKE PLATE MAY BE REMOVED  
NO OTHER MODIFICATIONS WHAT SO EVER
- B. CARBURETOR MUST PASS GAUGE TEST, TOP AND BOTTOM
- C. 1" ADAPTER PLATE ALLOWED
- D. MUST HAVE 2 RETURN SPRINGS
- E. CARBURETOR WILL BE SUBJECT TO RESTRICTER PLATE
- F. NO XP OR EXOTIC CARBURETORS
- G. PERCEY PLATE ARE ALLOWED

## 10. INTAKE MANIFOLD

- A. 2 OR 4 BARREL CAST IRON INTAKE, UNMODIFIED NO HIGH RISE 2 BARRELS
- B. NO BRAZINSKI INTAKES
- C. NO AFTER MARKET

## 11. EXHAUST

- A. 2 ½" DIAMETER MAXIMUM
- B. ANY STOCK PRODUCTION AND UNALTERED EXHAUST MANIFOLD ALLOWED. SHORT STYLE AFTERMARKET HEADERS WITH REDUCER ALLOWED. 1 5/8" TUBES MAXIMUM.
- C. NO PORTING AND POLISHING
- D. EXHAUST MUST EXIT BEHIND DRIVER
- E. NO H OR X AND 2 INTO 1 EXHAUST SYSTEMS

## 12. ENGINES

- A. CENTER LINE OF ENGINE MUST BE SAME DISTANCE FROM LEFT TO RIGHT FRAME RAIL
- B. ENGINE MUST BE US FACTORY PRODUCTION, CAST IRON BLOCK, HEADS, INTAKE,
- C. CYLINDER HEADS MUST BE 350 OR 305 HEADS UNMODIFIED NO DOUBLE HUMPS. 194 VALVES MAX, NO AFTER MARKET CYLINDER HEADS, ROLLER ROCKERS ALLOWED ALL MUST BE 1.5 OR 1.6 ALL MUST BE SAME SIZE, SCREW IN STUDS AND GUIDE PLATES ALLOWED. NO SHAFT MOUNTED ROCKERS. NO VORTEX OR ANGLE PLUG HEADS. STOCK VALVE SPRING SIZE.
- D. ENGINE SIZES: GM ENGINES 350 C.I. PLUS .060 MAX. OVER BORE (NO 400 BLOCK. FORD ENGINES 351 C.I. WINDSOR ONLY PLUS .060 MAX OVER BORE. MOPAR ENGINES 360 C.I. PLUS .060 MAX OVER BORE. NO CLEVELAND PARTS
- E. HYDROLIC CAM AND LIFTERS ONLY. 480 LIFT MAX.
- F. FLAT TOP PISTONS 2 OR 4 VALVE REFEIF
- G. NO LIGHT WEIGHT LOWER ASSEMBLIES.
- H. NO STOKING OR DESTROKING OF MOTORS
- I. ALL PART NUMBERS MUST BE LIGIBLE AND UNALTERED.
- J. NONE OF THE FOLLOWING PORTING, SANDING, POLISHING, GASKET MATCHING, GEAR DRIVES.
- K. STOCK APPEARING OIL PAN
- L. NO LS MOTORS
- M. CRANK SHAFT MUST WEIGH 49 LB
- N. INSPECTION HOLE IN OIL PAN BELOW DIP STICK HOLE, NO HIGH RISE INTAKES
- O. MINIMUM OF 54CC HEADS
- P. CHIP MAY BE ADDED AT ANY TIME

## 13. SAFETY ITEMS

- A. RADIO MANDATORY. ONE-WAY RECEIVER ONLY. ANY COMMUNICATIONS BETWEEN PIT CREW AND DRIVER WILL RESULT IN COMPLETE DISQUALIFICATION AND LOSS OF POINTS FOR THE SEASON.
- B. ROLL CAGE. MINIMUM 4 POST CAGE WITH 1 3/4" BY .095 INCH WALL THICKNESS MAY PASS THROUGH FIREWALL. DIAGONAL SIDE TO SIDE BRACING. FRONT AND REAR HOOPS MAY BE USED. MUST HAVE SEAL SUPPORT BAR BEHIND DRIVE. EXTRA BRACE BARS RECOMMENDED BEHIND DRIVER. MAY PASS THROUGH FIREWALL. MUST HAVE A 1/8" STEEL PLATE BETWEEN DOOR SKIN AND SIDEBARS. MINIMUM OF 3 DRIVER SIDE BARS, 2 BARS PASSENGER SIDE. GAS TANK PROTECTION BAR ANDATORY
- C. COMPETITION SHOULDER HARNESS AND SEAT BELTS MUST BE INSTALLED TO TECHNICAL INSPECTORS APPROVAL. SEAT BELTS AND SHOULDER HARNESSES OF THE 5 POINT VARIETY MUST BE USED AND SHOULD BE BOLTED TO THE ROLL CAGE STRUCTURE. LAP BELTS AND SHOULDER HARNESSES ARE TO BE 3" IN WIDTH. UPPER END OF THE SHOULDER HARNESS MUST BE SECURELY FASTENED TO METAL SUPPORTS AT A POINT NO HIGHER THAN THE DRIVERS SHOULDERS.
- D. THE FOLLOWING SAFETY EQUIPMENT IS MANDATORY,

E. FIRE SUIT, FULL COVERAGE HELMET MEETING SNELL STANDARDS, FIRE RETARDANT GLOVES. FIREPROOF SHOES ARE STRONGLY RECOMMENDED.

F. OPEN FACE HELMET MUST WEAR GOGGLES

G. DRIVERS SIDE WINDOW NET MANDATORY MUST BE MOUNTED TO CAGE NOT TO BODY PANELS

H. ANY ITEMS NOT COVERED SHOULD BE CHECKED WITH TECHNICAL INSPECTOR

I. NO OFF SET ROLL CAGES

#### 14. TRANSPONDER

A. IT IS HIGHLY RECOMMENDED THAT YOU PURCHASE YOUR OWN TRANSPONDER WESTHOLD TRANSPONDER, FOUND THEM ONLINE AT PIT STOP USA.COM RECHARGABLE WITH CHARGER IS \$225, OR WIRED IN IS \$169.

IF ANYTHING IS IN QUESTION CALL FOR CLAIRAFICATION BEFORE YOU DO IT . ANY ILLEGAL PARTS WILL BE CONFASCATED AND DESTROYED

#### PURSE

HEATS: 1-\$25, 2-\$20, 3-\$15, 4-\$10, 5-\$5

FEATURE: 1-\$150, 2-\$110, 3-\$100, 4-\$90, 5-\$85, 6-\$80, 7-\$75, 8-\$70, 9-\$65, 10-\$60,

11-\$55, 12-\$50, 13-\$45, 14-24-\$35