


VAPPRO VCI ROLL COAT

Function: Vapour Corrosion Inhibitor (VCI)	Application: Temporary Coating	Form: Liquid
------------------------------------------------------	------------------------------------------	------------------------

DESCRIPTION



VAPPRO VCI Roll Coat is a brown solvent-based thixotropic free-flowing liquid corrosion inhibitor. After the solvent has evaporated the residual film is highly resistant to salt environments making it particularly useful in marine, industrial, and offshore rust proofing applications.

VAPPRO VCI Roll Coat provides optimal corrosion protection for up to 12 months for ferrous and non-ferrous metals.

VAPPRO VCI Roll Coat offers excellent protection when shipping metal parts.

FEATURES

- Dry-to-touch film properties allow protected metal surfaces to be easily handled
- Little surface preparation needed as it adheres to pre-rusted surfaces
- A thixotropic free-flowing liquid
- Excellent UV protection
- The protective film will not crack or chip after extended exposures to sunlight
- Protects ferrous and non-ferrous metals and alloys
- Prevents galvanic corrosion between dissimilar metals
- Outstanding moisture displacing characteristics
- Provides up to 12 months outdoor protection in corrosive environments
- Contains penetrating film characteristics
- Easy to remove with **Magna Citra-Solv Degreaser**

APPLICATIONS

Maintenance

- Protection of structural plants and equipment
- Mothballing refineries, power plants, and chemical plants
- External surfaces of large machines, pipes, pumps, and heat exchangers during standby, field storage, or operation

Marine and Offshore

- Internal surfaces of offshore platforms and equipment
- Oil Tank storage
- Castings, pumps, valves, compressors, heat exchangers, boilers, turbines, and transformers
- External and internal surfaces of drill pipes and sucker rods

OEM

- Internal and external surface of engines
- Bearings, brake drums, and engine components
- Frames, cabs, stampings, castings and plate steel
- Transmissions, hydraulic pistons, cylinders, and equipment undercoating

PHYSICAL PROPERTIES

Appearance	Thixotropic liquid
Colour	Brown
Specific Gravity	0.92 at 25°C
Film type	Slightly tacky dry film
Carrier	Mineral Spirits
Flash point	232°C (Concentrate form)

DIRECTIONS FOR USE

- Recommended methods of application are dipping, spraying or brushing
- A minimum film thickness of 2-3 mil is recommended
- For maximum long-term protection coat with a 4-5 mil film
- **VAPPRO VCI Roll Coat** can be applied over pre-rusted or oily surfaces
- Application does not require heating or increased temperatures for drying

PACKAGING

- 20L Pail
- 200L Drum



Manufacturing Facility
1450 Government Rd., West
Kirkland Lake, ON
P2N 2E9 Canada

Contact Information
T: 1 (416) 479-9151
F: 1 (888) 317-1993
E: magna@vapro.com

Websites
www.vapro.com
www.vapro.ca