




**Fiber Optic Cable  
Furcation Tubing**  
Hytrel 900uM Furcation Tubing (for 250uM Fiber)



900uM OD x 500uM ID  
(0.035" X 0.020")

**Part Number:**

**722000-035XXX**

Replace XXX with:

- BLU - BLUE
- ORG - ORANGE
- GREEN - GREEN
- BROWN - BROWN
- GRY - GREY
- WHT - WHITE
- RED - RED
- BLK - BLACK
- YEL - YELLOW
- VIO - VIOLET
- PNK - PINK
- AQU - AQUA



**Mechanical:**

**Diameter:** 0.035" (900uM)

**Minimum Bend Radius:**  
2.0" (5cm) Installation  
1.2" (3cm) In Service

**Cable Weight:** 0.35lbs/1000ft (0.52kg/km)

**Operating Temperature:** -40C to 85C (-40F to 185F)

**Storage Temperature:** -40C to 85C (-40F to 185F)

**Construction**

**Component**

Tube: 0.035" x 0.020" (900uM x 500uM) Elastomer (Hytrel)  
Tubing Color: To TIA/EIA-359: Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Aqua

**Applications Note:**

This tubing is designed for upjacketing 250um fiber to 900um fiber for direct termination or splicing applications.

[www.opticonx.com](http://www.opticonx.com)

Drawn By: PCS  
Approved By: PL  
Date: 10/10/14  
Rev: A

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Opticonx, Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Opticonx, Inc. IS PROHIBITED.