



RENTAL UNIT
400,000 to 3.5 million BTU

Afterburner
Direct Fired Heaters

PRODUCT FEATURES

Body Construction.....Stainless Steel
 Burner.....Stainless Steel
 Consumption Rating.....High Efficiency
 Fuel Type.....Natural Gas/LPG Fired
 Sizes..... 400,000 to 3,500,000 BTU

APPLICATIONS:

- Job Site/Construction Heat
- General Building Heat
- Temporary Shelter
- Industrial Heat
- Commercial and Institutional Heating

TECHNICAL DATA/SPECIFICATIONS

Model	Output	Manifold Pressure	Max. Gas Consumption	CFM	Electrical	Weight
400K	High 400,000 BTU Low N/A	2" W.C. LPG 7" W.C. NG	4 Gallons/hr 400 CFH	2800	1/4 hp motor 120V, 3 amps	90 lbs
700K	High 700,000 BTU Low 250,000 BTU	2" W.C. LPG 7" W.C. NG	7.5 Gallons/hr 700 CFH	4500	1 hp motor 120V, 8 amps	178 lbs
1.5M	High 1,500,000 BTU Low 800,000 BTU	2" W.C. LPG 7" W.C. NG	15 Gallons/hr 1500 CFH	7600	1 hp motor 120V, 16 amps	305 lbs
2.0M	High 2,000,000 BTU Low 1,000,000 BTU	2" W.C. LPG 7" W.C. NG	20 Gallons/hr 2000 CFH	8000	1.5 hp, 120V, 14 amp 230V, 480V available	355 lbs
3.5M	High 3,500,000 BTU Low 1,000,000 BTU	9" W.C. LPG 14" W.C. NG	35 Gallons/hr 3500 CFH	21,000	5 hp, 480V, 8 amp 5 hp, 230V, 21 amp	540lbs

Consult your Caterpillar representative for more details.

www.CAT-ElectricPower.com

©2003 Caterpillar
 All rights reserved.
 Printed in U.S.A.

LEHX3879 (1-03)

Materials and specifications are subject to change without notice.

