



TOP LID

HEIGHT (IN.)	WEIGHT (LB.)
6	675

RISER WEIGHT

HEIGHT (IN.)	WEIGHT (LB.)
10	625
24	1500
30	1875
36	2250
42	2625
48	3000

BASE WEIGHT

HEIGHT (IN.)	WEIGHT (LB.)
36	2322

*** CUSTOM PRODUCT SIZES ARE AVAILABLE UPON REQUEST. PLEASE CALL (865) 458-3998 FOR A TECHNICAL SERVICE REPRESENTATIVE.

GENERAL NOTES:

1. ALL MATERIAL, DESIGN, MANUFACTURE, PHYSICAL TEST REQUIREMENTS, FINISH MARKING, INSPECTION, REJECTION AND REPAIRS TO MEET ASTM'S C913, C857, AND C890 (CURRENT EDITIONS)
2. CONCRETE STRENGTH: f'_c @ 28 Days = 5,000 psi
3. EXPOSED EDGES HAVE A $\frac{3}{4}$ " CHAMFER
4. REINFORCING STEEL MEETS ASTM A-615, GRADE 60 WITH 1" MINIMUM CONCRETE COVER.

VANHOSECO PRECAST, LLC

244 BLAIR BEND DRIVE
 LOUDON, TN 37774
 Tel: (865) 458-3998



24"x24" WITH KNOCKOUTS
 CATCH BASIN

SCALE: 1/2" = 1'-0"

CB7