

WL290

High performance water dispenser
for great quality water



Superior performance

The WL1000GF Max is able to satisfy high demand of cold water, even at peak times, dispensing high volumes of perfectly chilled water.

Advanced technology

The WL290 features three core technologies:



High Performance Filtration

This model can be configured with four stages reverse osmosis filtration or multi stage carbon filtration, depending on water conditions. These filtration processes effectively remove water contaminants and chlorine to improve water taste and odor.



In-tank UV*

Waterlogic's UV technology uses an in-tank UV system to effectively remove waterborne micro-organisms to guarantee the best quality water.



BioCote® protection

The water reservoir and the plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive able to protect the product against the negative effects of odor and staining microbes, such as bacteria and mold.

Simply great, clear water*

Free from fluoride (dependent on filters type and water conditions)

Free from chlorine (dependent on filters type and water conditions)

Free from water-borne tastes and odors

*Filtration results based on the use of RO, GAC, CBC or sediment filters.

The new WL290 satisfies the needs for high volume of cold and hot water, whilst delivering superb quality water. Specifically designed for water conditions when reverse osmosis is needed, or where there might be low water pressure, the WL290 is a gravity fed machine with premium filtration and in-tank ultraviolet light built in, able to dispense the best tasting water. The improved internal design and technology makes the WL290 perfect to supply quality water all day long in high traffic working environments and public places.

Features

Multiple filtration options: choice of reverse osmosis or carbon filtration to fit local water conditions
Large chilled recirculating reservoir for high capacity cold water production: the improved design allows for 4x more cold water capacity
Gravity-fed storage tank providing additional stored water for the reverse osmosis system or for low pressure installations
The recirculating cold water system passes water by the in-tank UV light multiple times every hour to maintain the microbiological purity of the water
Programmable temperature settings for hot and cold options
GAC filter fitted inside the cold reservoir to provide ongoing protection from bad taste and odors
Fault indications for easier servicing
BioCote® protected reservoir and dispensing area (including drip tray body, cold faucet, user interface panel and buttons)

Water options

cold	sparkling	ambient	hot	extra hot
				

Number of users

50+ 

Tested and certified



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Technical specifications

Type available

Freestanding

Dimensions

15.5" (W) x 46" (H) x 14.5" (D)

Dispense area height

9.0"

Weight

62 lbs

Recommended filtration

Reverse Osmosis or 1 x Carbon Block (CBC), Sediment, GAC, CBC with lead and cyst removal (dependent on local water conditions)

Additional features

Leak detection
Hot and cold fault detection
Pump fault detection
Programmable filter timer (6, 9, 12 months or none)
Sleep mode on/off

Storage capacity

Chilled reservoir: 11.2 liters (~ 3 gal.)
Cold hybrid tank: 4 liters (~ 1 gal.)
Total cold capacity: 15.2-liter (~ 4 gal.)
Hot tank (500 Watt): 1.5 liters (~ ½ gal.),
185° F thermistor-controlled

Dispensing capacity (Cold)

More than 2 gallons (7.6 liters) per hour

Compressor

1/10-hp, 90-Watt

Pump recirculation rate

1 liter per minute

Programmable water temperatures settings

Cold: 37°/ 41°/44° F (default set at 41°F)
Hot: 176°/ 185°/ 199° F (default set at 185°F)

Call us today

Waterlogic USA

100 Biddle Ave, Suite 203
Newark, DE 19702

Tel: 844-854-7279

info@waterlogicsusa.com
www.waterlogicsusa.com

For more information, visit www.waterlogic.com