



LOCATE WIRE MUST BE STRIPPED AND CONNECTED TO TAPPING TEE OR "MEGALUG" BOLT IF EXISTING MAIN DOES NOT HAVE LOCATE WIRE. IF LOCATE WIRE EXISTS, USE WATERPROOF SPLICE TO CONNECT WIRES.

- NOTE:**
1. "MEGALUG" OR "UNI-FLANGE" JOINT RESTRAINTS ONLY.
 2. "GRIPPER GASKET" IS REQUIRED ON ALL BELL/SPIGOT JOINTS WHERE THE DISTANCE BETWEEN BELL/SPIGOT JOINT AND ANY MJ FITTING IS LESS THAN 20'.
 3. ALL PARTS MUST BE APPROVED BY BSWSD 363.
 4. THRUST BLOCKS MAY BE REQUIRED AT THE DISCRETION OF BSWSD 363.

| | | | | |
|---|---|---------------------------|---|---|
| DETAIL NO.: BSWSD: 26-11 | BIG SKY WSD 363 STANDARD DRAWING | SCALE: NONE | WATER MAIN CROSSING BELOW EXISTING SEWER MAIN | DATE: FEBRUARY 2010 |
| | | | | LAST REVISION: JANUARY 2020 |
| | | | | CROSS REFERENCE WITH: COB: 02660-11 |