

Ceramic Coating Aftercare Instructions

- Do not clean the coated surface of the vehicle for at least 5-10 days after the coating has been applied. This is to allow full curing of the coating.
- Avoid water contact for 4 hours after coating (includes morning dew).
- When you do wash your vehicle, a good, high-end, proper hand wash is highly suggested. The surface of your vehicle is now more resistant to light scratches and chemical etching, but it is not scratch proof. Harsh chemicals and washing techniques from automated touch and touchless car washes will still damage the coating and reduce its lifespan. Do not use automatic carwashes.
- If you choose to wash your car yourself or hire a good mobile detailer, we recommend that it is always washed by hand in the shade (no direct sunlight). Use the following suggested products for best results...
 - P&S Detail Products Pearl Car Wash Shampoo or Griot's Garage Brilliant Finish Car Wash.
 - The Rag Company Cyclone Microfiber Wash Pad or Griot's Garage Microfiber Wash Pad.
 - The Rag Company Gauntlet Microfiber Drying Towel or Griot's Garage PFM Terry Weave Drying Towel.
- Ceramic Coatings not only make your car look better, but they help it stay cleaner longer and make your car easier to clean, but they are NOT maintenance free. For your coating to perform its best and last as long as possible, we recommend the application of a paint sealant every 4 (parked outside) to 6 (garaged) months...
 - P&S Bead Maker Paint Protectant or IGL Ecocoat Premier.
 - The Rag Company Eagle Edgeless 500 Microfiber Towels or Griot's Garage Microfiber Plush Edgeless Towel.
- Bird poop, tree sap and bug guts are corrosive to your paint and the ceramic coating, and must be washed off immediately. Industrial fallout, iron deposits and road grime should be removed regularly as part of your maintenance wash routine.