

Hardcore Derby Promotions 2021 Bone Stock class Rules

Rust repair should be kept to a minim with same thicknesses with a 1-inch overlap and be stitch welded

- Stock means stock. No shaping the body panels or frames. NO welding to the car unless specified in the above rules. If it doesn't state that you can then you can't. Questions, please call

Frankie Guy 724-557-7428

Charlie Post 724-350-5984

Justin Hartzell 304-559-7893

This class is to be EZ and simple. please do not push or try to read into this set of rules, let's keep it simple and have fun with this, please any questions CALL FIRST

Officials interpretation of the rules and Decisions are Final

Hardcore Derby Promotions 2021 Bone Stock class Rules

- : A bar may be placed behind the driver's seat B post and may extend from side to side. This bar may not exceed 2"x6" or 4"x4" diameter round or square. Each end of the bar may have a 12"x12" piece of flat stock steel. The bar may be welded into place. Drivers door May also be Plated, Plate may not exceed Drivers door more than 3" inches. The A pillar bar may be put in the same way as B pillar bar. No other bars are allowed anywhere on car.
- Doors can be secured shut by 9 wire(2 strands), chain 1/4" or 3"x3"x 1/8 patches in 8 spots max doors may be secured shut. Sheet metal to sheet metal, No Chains Can be welded No other form of securing doors shut will be allowed.
- Trunks and tailgates must be secured shut with 9 wire (2 strands) chain 1/4", or 3"x3"x1/8 patches.6 spots max to secure trunk lid shut. Sheet metal to sheet metal ONLY! No other form of securing hood shut will be allowed.
- There must be a 8"x8" inspection hole cut in the trunk lid. No crushing trunk lid down. Stock position. You may 9 wire 2 strands in 4 spots to the rear bumper.
- Hoods must be secured shut with 9 wire, (2 strands)1/4 chain, or 1/2 bolts in 4 spots max.the hold downs may pass through top of core support or sheet metal only
There must be a 8"x8" hole cut in center of hood in case of a fire. No other form of securing hood shut will be allowed!
- A bar (2" wide max) must be attached in the windshield are from the roof to the firewall cowl. No more than No more than 3" overlap on to cowl and roof
- All cars must have dependable brakes at all times.
- Rear end gears maybe weld for posi traction.
- Any tire will be allowed, skid steer tires are allowed. Tubing tires are allowed. Only small weld in centers rims will be allowed with no modifications allowed.
- Rear frame rails maybe notched, but not Pre bent to achieve bend. No welding of the frame when notched.
- Bumper
 - shocks front and rear maybe collapsed and re welded around. Or You may use 2 pieces of 2"x6"x1/4" per side and hardnose bumpers to frame Bumpers should be wired or chained in 2 places to the 1st 3 inches of front frame rail. If Hardnosing nothing can be inside of frame
 - Bumpers if that aren't welded to frame, they must be wired or chained to frame, in 2 places to the 1st 3 inches of frame we do not want to stop the derby every 5 minutes to pick up bumpers
 - Bumpers maybe swapped for a 1980 and newer car bumper. No stuffing or seam welding of bumper allowed.
- sheet metal or steel maybe cut and removed no bolts added to cut sheet metal, nothing maybe added to Frames unless specified. Frames may not be shortened in anyway.

Hardcore Derby Promotions 2021 Bone Stock class Rules

Any 1980 or newer Automobiles. NO hearse, limousines, special service, propane cars FWD, SUV'S, all-wheel drive or 4 wheel drive or Checker Cabs.

GENERAL RULES

- All glass, plastic and pot metal and fiberglass must be removed. Nothing may remain in the bottoms of the trunk and doors ,car must be swept clean of all debris and glass
- All - door handles, mirrors, chrome, moldings, screws, fiberglass, etc.
- Rear seats, carpets, door panels headliners must be removed and all decking in station wagons must be removed.

You must have a functioning seat belt. Make sure it works !!

- All flammable materials must be removed from the car other than safety padding on the driver's seat. DASHES AND WIRING MAY BE LEFT INTACTE.
- Air bags must be removed if car is equipped with them
- Engine, transmission, suspension, shocks, rear end and cross member must be factory and Remain in the factory stock position and manner for that year model and make. Suspension must work up and down only the screw in risers permitted in coil springs
- Cars with column shifters must remain on the column
- All original gas tanks must be completely removed. Your gas tank/fuel cell must be mounted securely in back seat area or to rear seat bar. No bungee cords or generic metal straps or seat belts allowed to secure tanks. No Exceptions! No Plastic Tanks!!!
- Battery (1 car battery only) Must be moved to passenger front floor board. Battery must be secured to floor board. No bungee cords or generic straps(Battery Box Highly Recommended)to secure battery. Battery must also be covered.

If computers (etc.) is mounted in fender well it may be mounted to the top of the engine. It may not be mounted in car or cowl. Spray foam maybe used to hold computer