

VERTICAL TILLAGE SPECIFICATIONS

MODELS: FURY HS.250 / HS.300 / HS.350 / HS.400

8" BLADE SPACING	VT290 (8" SPACING)	VT290 (9" SPACING)	VT320 (8" SPACING)	VT320 (9" SPACING)	VT345 (8" SPACING)	VT345 (9" SPACING)	VT375 (8" SPACING)	VT375 (9" SPACING)
DIMENSIONS								
Width, working	28' 10" (8.8m)	28' 10" (8.8m)	31' 7" (9.6m)	32' (9.8m)	34' 2" (10.4m)	35' 2" (10.7m)	36' 11" (11.3m)	38' 4" (11.7m)
Width, transport	17' 3" (5.3m)	17' 3" (5.3m)	17' 3" (5.3m)	17' 3" (5.3m)	17' 7" (5.4m)	17' 10" (5.4m)	17' 7" (5.4m)	17' 10" (5.4m)
Height, transport	13' 8" (4.2m)	13' 8" (4.2m)	14' 6" (4.4m)	14' 6" (4.4m)	14' 8" (4.5m)	15' (4.6m)	16' (4.9m)	16' 3" (5.0m)
Weight class	800 lb/ft class (1190 kg/m)							
Horsepower required (drawbar)	8 - 12 hp/ft (20 - 29 kW/m)							
Working depth	0 - 5 in (0 - 127 mm)							
Working speed	7 - 10 mph (11 - 16 km/hr)							
STRUCTURE								
Frame, main frame	8" x 4" x 0.5" (203 x 102 x 12.7 mm)							
Frame, cross member	6" x 4" x 0.5" (152 x 102 x 12.7 mm)							
Bearings	T2-215 extreme duty series							
Gang angle, adjustable	0, 4, 8, 12°							
Gang shaft	1-15/16" (49 mm) high carbon steel							
Gang shaft, factory torqued	3,200 ft/lb (4339 N-m)							
BLADES								
Blades, standard	22" x 1/4" (508 x 6.5 mm) SoilRazor™							
Blades, optional	24" x 1/4" (560 x 6.5 mm) SoilRazor™							
FEATURES								
Tires, main frame	FS24 380/55R16.5 radial tires (290 and 320 models) FS24 440/55R18 radial tires (345 and 375 models)							
Tires, wing frame	12.5L x 15 implement tires							
Depth control	3-cylinder series system c/w depth stop segments Optional single point hydraulic depth control							
FINISHING TOOLS								
Rolling baskets	12" (305mm) diameter w/8-spiral flat bars							
Tine harrows	3-bar mounted							
4x4 tool mounting bar	Allows for any finishing							
* Working width measured up to the furrow filler blade at 8 degrees of gang angle.								

NOTE: Specification are correct at time of publishing and are subject to change

