



# DecoSeal

Clear Coat Sealer—MATTE or GLOSS

## FEATURES BENEFITS

<b>Dries to a clear appearance</b>	Available in Matte or Gloss finish
<b>Ready-Mixed</b>	Ready to use on site; no additional additives needed
<b>Low VOC</b>	Environmentally safe
<b>Water-Based</b>	100% acrylic, Safe, non-toxic; cleans up with water
<b>Vapor permeable</b>	Allows substrate to breathe naturally
<b>Abrasion/Mar resistant</b>	Increased abrasion resistance
<b>Dirt Pickup Resistant</b>	Stays cleaner longer

## SURFACE PREPARATION

All surfaces must be fully cured, structurally sound and free of weak or damaged surface conditions such as laitance or spalls. Surfaces must be clean, dry, frost-free, and free of any bond-inhibiting materials such as dust, dirt, oil, form release, algae, mildew, salts, efflorescence, or any other surface contamination.

## MIXING

Mix with a clean, rust-free electric drill and paddle to a uniform consistency. Close container when not in use. Clean tools with water immediately after use.

## APPLICATION

Apply only in well-ventilated areas to structurally sound, clean, dry, properly prepared and primed, frost-free surfaces.

**IMPORTANT!** Always construct a mock-up under actual conditions of use to verify proper surface preparation, number of coats required, and approval of finished look by the appropriate authority.

DecoSeal is applied by roller with 2 thin coats, allow DecoSeal to dry between coats approximately 2—3 hours @ 70° f and 50% RH. Protect from freezing for a minimum of 24 hours after application. Drying time will vary based on ambient air conditions, increased humidity and lower air temperatures will increase cure time. Avoid application in cool damp conditions.

## TECHNICAL DATA

REPORT	TEST METHOD	TEST CRITERIA	TEST RESULTS
VOC (g/L)			This product complies with US EPA (40 CFR 59) and South Coast AQMD (Rule 1113) VOC emission standards for architectural coatings. VOC less than 50 g/L.

*DecoSeal is a 100% acrylic formulated clear coat sealer with either a Matte or Gloss finish. It dries to a clear appearance, reduces dirt pickup resistance and cleans up easily with water.*

*It provides a surface barrier to resist UV, acid rain and other environmental pollutants. It improves the water and freeze thaw resistant of porous exterior surfaces by lowering water absorption.*

### Coverage

Coverage depends on the texture and porosity of the surface/substrate. For sealing new applications, the coverage is approximately 1200—1600 ft<sup>2</sup> per pail.

### Packaging

5 gal pail (19L) 40 lbs. / 18 kg per pail

### Shelf Life

2 years from date of manufacture when properly sealed and stored.

### Storage

DecoSeal must be stored at a minimum of 50°F (10°C) in tightly sealed containers protected from weather and out of direct sunlight.



# DecoSeal

Clear Coat Sealer—MATTE or GLOSS

## APPLICATION CONTINUED

### Curing/Drying

The drying time of DecoSeal is dependent upon the air temperature and relative humidity. Under average drying conditions (70°F (21°C), @55% R.H.), DecoSeal is dry to the touch in 2 hours. Protect work from rain for at least 24 hours.

### Clean Up

Clean tools and equipment with water immediately after use. Remove dried material from tools and equipment mechanically.

## LIMITATIONS

Use DecoSeal only when surface and ambient temperatures are above 40°F (4°C) and below 100°F (38°C) during application and drying period.

Re-Sealing may be required based on exposure to extreme elements.

Not intended for substrates exposed to hydrostatic pressure, periodic or continuous water immersion

Store Decoplast materials in a cool, dry place.

Sloped surfaces: Refer to Decoplast details.

DecoSeal should not be used on weather-exposed horizontal or below grade surfaces or where immersion in water may occur.

Do not apply DecoSeal to frozen surfaces.

## HEALTH AND SAFETY

### Health Precaution

Decoplast DecoSeal is water-based. As with any chemical construction product, exercise care when handling.

### WARNING!

Causes eye and skin irritation.

### Safety Precaution

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

### First Aid:

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eye lids with fingers. Get immediate medical attention.

**SKIN CONTACT:** Immediately wash skin with plenty of soap and water for at least 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

**INHALATION:** If inhaled, remove to fresh air. If not breathing give artificial respiration or give oxygen by trained personnel. Seek medical attention immediately.

**INGESTION:** If swallowed, do NOT induce vomiting. Call a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.

### Spills

Contain and clean with appropriate absorbent materials.

### Disposal

Dispose of in accordance with local, state or federal regulations.

### Warning

KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet (SDS) for further health and safety information.

### LIMITED WARRANTY

This product is subject to a written limited warranty. Refer to Decoplast Specifications for more complete information on proper use and handling of this product.



697 Oakwood Avenue, West Hartford, CT 06110  
voice: 860.761.2830 fax: 860.761.2831  
www.decoplast.com

This product is intended for use by qualified professional contractors. All information conforms to the standard detail recommendations and specifications for the installation of Decoplast systems and is presented in good faith as of the date of publication of this document. GREENMAKER INDUSTRIES ASSUMES NO LIABILITY, EXPRESSED OR IMPLIED, AS TO THE WORKMANSHIP, ENGINEERING OR ARCHITECTURE OF ANY PROJECT. For more information regarding this product or additional Decoplast products, please contact a Decoplast Representative at (860) 761-2830 or visit our website [www.Decoplast.com](http://www.Decoplast.com).