

# FE-1 Series

## LED Architectural Marker Light

Type:

Catalog Number:

Project/Location:

Approved By:

### SPECIFICATIONS

**Housing:** Heavy-duty construction of corrosion resistant formed steel. Stainless steel hardware.

**Face Plate:** Aluminum.

**Gasket:** Closed cell silicone foam gasket. Seals out moisture, dust, and insects for weather-tight operation.

**Mounting:** Recessed wall.

**Lens:** Diffused acrylic lens.

**Driver:** Solid state electronic constant current. Input voltage 120V or 277V.

**LED:** Specify amber (A), blue (B), green (G), red (R), or 3000 (30K), 3500 (35K), 4000 (40K), and 5000K (50K). 40K Standard.

**Lumens:** 100.

**Finish/Colors:** Zinc based primer with polyester powder coat finish in Matte Black (MB), Matte White (MW), Matte Bronze (BZ), Silver Gray (SG), or a custom color (CC). SG standard.

**Testing:** LM79, LM80, ETL.  
Suitable for damp locations.

*See options page for additional information or consult factory.*




Series	Source	Wattage/Max
FE-1	LED	1W

### ORDERING EXAMPLE


FE-1 – 1WLED – 40K – 120 – SG



FRONT



SIDE



## ELCAST LIGHTING

815 S. Kay Ave., Addison, IL 60101 USA • 630.543.5390  
www.ElcastLtg.com • ElcastLtg@ElcastLtg.com

**Made in USA** – 5 year limited warranty

©2017. Specifications are subject to change without notice. Consult factory for verification.

REV 01-19