

BR-6144 Series

LED Architectural Column

Type:

Catalog Number:

Project/Location:

Approved By:

SPECIFICATIONS

Housing: Heavy-duty construction of corrosion resistant round and rectangular aluminum extrusions. Stainless steel hardware.

Gasket: Closed cell silicone foam gasket. Seals out moisture, dust, and insects for weather-tight operation.

Mounting: Integral base secured with 3/4" x 17 anchor bolts.

Lens: 1/8" thick UV stabilized frosted acrylic lens. Aluminum lamp housing.

Driver: Constant current and Universal input voltage 120-277V, 50-60Hz line voltage frequency. Operating temperature -20°C to 40°C, Power Factor $\geq .90$.

LED: 3000 (30K).

Lumens: 4500.

Finish/Colors: Zinc based primer with polyester powder coat finish in Matte Black (MB), Matte White (MW), Matte Bronze (BZ), Silver Gray (SG), or a custom color (CC).

Testing: LM79, LM80, ETL.

Conforms to UL Standard 1598. Suitable for wet locations.

See options page for additional information or consult factory.

60W, 120 V symmetric distribution.





EMERGENCY BATTERY
BACKUP AVAILABLE

| Series | Source | Wattage/Max |
|---------|--------|-------------|
| BR-6144 | LED | 60 |

ORDERING EXAMPLE

BR-6144 – 60LED – 30K – 120 – BZ



±10 5/16"±

ELCAST LIGHTING

815 S. Kay Ave., Addison, IL 60101 USA • 630.543.5390
www.ElcastLtg.com • ElcastLtg@ElcastLtg.com

Made in USA – 5 year limited warranty

©2017. Specifications are subject to change without notice. Consult factory for verification.

REV 02-19