

# BRT-40 Series

## LED Bollard

Type:

Catalog Number:

Project/Location:

Approved By:

### SPECIFICATIONS

**Housing:** Heavy-duty construction of corrosion resistant extruded and aluminum. Stainless steel hardware. Top (canopy) is removable.

**Gasket:** Closed cell silicone foam gasket. Seals out moisture, dust, and insects for weather-tight operation.

**Mounting:** Secures with 3/8" x 6" galvanized anchor bolts.

**Lens:** 1/8" thick UV stabilized clear polycarbonate lens.

**Driver:** Constant current and Universal input voltage 120-277V, 50-60 line voltage frequency. Operating temperature -20°C to 40°C, Power F  $\geq$  .90.

**LED:** Specify amber (A), blue (B), green (G), red (R), or 3000 (30K), 3500 (35K), 4000 (40K), and 5000K (50K). 40K Standard.

**Lumens:** 1530.

**Finish/Colors:** Zinc based primer with polyester powder coat finish in Matte Black (MB), Matte White (MW), Matte Bronze (BZ), Silver Gray (SG), or a custom color (CC).

**Testing:** LM79, LM80, ETL.

Conforms to UL Standard 1598. Suitable for wet locations.

*See options page for additional information or consult factory.*




EMERGENCY BATTERY  
BACKUP AVAILABLE

Series	Source	Wattage/Max
BRT-40	LED	18W

### ORDERING EXAMPLE

BRT-40 – 18WLED – 40K – UNV – SG



## ELCAST LIGHTING

815 S. Kay Ave., Addison, IL 60101 USA • 630.543.5390  
www.ElcastLtg.com • ElcastLtg@ElcastLtg.com

Made in USA – 5 year limited warranty

©2017. Specifications are subject to change without notice. Consult factory for verification.

REV 09-18