



## A Study on Application of Coordinate Measuring Machine in Flexural Manufacturing System

<sup>1</sup>Shreyash paneliya, Urviskumar Bharti, <sup>2</sup>M. Ramachandran

<sup>1</sup>MPSTME, SVKM'S NMIMS University, Shirpur, Dhule, Maharashtra, India

<sup>2</sup>REST Labs, Kaveripattinam, Krishnagiri, Tamil Nadu, India

[sweetestchandran@gmail.com](mailto:sweetestchandran@gmail.com)

### Abstract

In this paper, we are discussing about CMM (Coordinate Measuring Machine), Calibration, Error compensation, Laser tracker, Sampling strategy, Touch probe. A coordinate measuring machine (CMM) is an instrument which can measure the shape/layout/figure of any machine-parts or physical body which can be done by sensing discrete locations on the plane of the machine-part or physical body by using a probe. Different kinds of probes are utilized in CMMs, i.e. mechanical, optical, laser, and white light. Co-ordinate estimating machines (CMMs) can be utilized as such instrument for assortment of alignments. So as error compensation method is explored to enhance the accuracy of Coordinate Measuring Machine (CMM). Errors origins examinations, error modelling and errors computation, these are basic steps of error compensation. Coordinate Measuring Machine (CMM) has been a significant assessment instrument in quality control for quite a while attributable to its inflated precision & accuracy. Effectiveness of inspection plan initiated CMM enormously relies on measurement duration. The laser tracker is a huge scope compact estimating device having high precision which can compute the points of any work-piece in convex focuses. The sampling methodology contains the ideal sample size and the points of the sampling focuses. A touch trigger test has a pointer that is connected to a bearing plate. This is then associated (attached) with pressure sensors inside the housing of the probe. Each time the probe connects with the work piece, it produces an electrical signal, then signal is sent back to the CMM to make exact measurements.

Keywords: about CMM (Coordinate Measuring Machine), Calibration, Error compensation, Laser tracker, Sampling strategy, Touch probe.


### 1. Introduction

A coordinate measuring machine is a gadget which can quantify the math of physical items, detecting discrete focuses on the outside of the article with a test. Facilitate estimating machines (CMMs) are generally utilized in assembling and plan. By ISO 10360-1 CMM is distinguished by as an estimating framework with the way to move an examining framework and the capacity of deciding spatial directions on a work piece surface. CMMs are generally acknowledged to quantify the three-dimensional sizes, structures, and places of fabricated parts. These machines can be unsupported, handheld and compact. It is the way toward confirming and modifying the precision of Measuring and Monitoring Equipment and machines by contrasting them and principles of known exactness. Alignment gives the certainty that their precision is according to the given particular of OEM. The proposed self-alignment technique utilizes an antiquity, a ball plate, for mistake recognizable proof. Adjustment acted in ordinary stretches in order to guarantee that the instrument is solid. The alignment of CMM is performed by the rules gave in ISO 10360-2. Velshis et al. [17] executed neural organizations in a blunder pay system for machining with a five tomahawks machine. The decision of an Error remuneration procedure relies by and large upon the kind of regulator utilized or accessible on the machine, and its adaptability. The CMM programming empowers clients to change the boundaries for blunder pay. The current work manages the examination of freestyle surfaces having a place with no rigid parts. Non rigid freestyle surfaces are of incredible enthusiasm for some applications, since they are assuming an expanding function in item plan. Investigates endeavours on assessment techniques for freestyle surfaces have been accounted for in writing. This paper thinks about the use of hereditary calculations (GAs) going about as optimisers for ideal assessment way arranging frameworks. Hereditary calculations have been advanced as a class of broadly useful inquiry methodologies that move through complex space in a close to ideal way. Organize Measuring Machine (CMM) has been a significant examination apparatus in quality control for quite a while inferable from its high exactness and accuracy. Viability of investigation plan produced by CMM enormously relies upon estimation process duration. Minor the examination time taken by CMM to evaluate a given

part finer will be the exhibition of assessment measure. So as to grow new measures and elective alignment and check strategies related to AACMM, in that the investigation of the utilization of a laser tracker as a kind of perspective device in the adjustment and confirmation methods of AACMM supplanting the regular one-dimensional measures as ball bars is introduced. The essential improvements of estimation reliant on laser tracker applied to exactness examination for robot's returns to the 1980s. In any case, as of late the dimensional confirmation for huge reach structures in mechanization or flight related area has thrust ahead and laser tracker innovation is becoming considerably throughout the most recent 15 years. Test size (the quantity of focuses estimated) is normally corresponding to time and cost and for a given examining system. The testing methodology chose assumes a significant function since it empowers to make legitimate inductions about measurements and types of a work piece. Another touch test having a three degrees-of-opportunity power sensor is initiated. Powers and minutes act at the foundation of the test head because of the estimating power and it can be distinguished by the created five-dimensional power/force transducer. The vulnerability of contact between the cone-formed pointer and the bundles of antique is 3wm, and the vulnerability of rotating encoder is 3 heartbeats. Portrays a procedure for vulnerability appraisal for Coordinate Measuring Machine estimation of complex genuine work pieces from industry. In general outcomes are summed up in the deviations from the reference esteems. Mistake bars speak to the vulnerability detailed by the members, while the spotted red lines speak to the vulnerability of reference esteems.

## 2.CMM

Coordinate measuring machines (CMMs) are amazingly incredible metrological instrument for quantifying the solid mathematical attributes of a work piece. CMMs are broadly utilized in assembling. CMMs are used in layout also. A developing pattern in dimensional examination of fabricated work-piece is the utilization of non-contact laser digitizers rather than contact probes. The laser digitizer proposed the benefits of no contact distract force, and data assortment paces of millions of focuses every second. [16].



Coordinate measuring machine (CMM) is the most significant universally useful instrument to measure freestyle shapes in industry. By ISO 10360-1, coordinate measuring machine is characterized as a measuring system. Including to move a probing system and the ability of deciding structural positions(coordinates) on a work-piece surface. CMMs are generally used to estimating the three-dimensional sizes, structures, and coordinates of made objects. In any case, CMM measurement mistake happens when there is an error in the relative coordinates between the measured focuses and the probing focuses. The error influencing a precise and a random part of the CMM. It will also straightforwardly impact the standard of assembly. Accordingly, CMMs should be calibrated on establishment intermittently when CMMs are in working state. For the verification of CMMs, there are numerous techniques are created to. Most std. like to utilize end principles, for example, a step gauge, a series of gauge blocks and a ball plate or laser interferometer. [22]. A precise coordinate measuring machine is a significant apparatus device to estimating geographical coordinates. It is such a high precision and acute measuring machine that fuses mechanical, electrical, optical, mathematical control and automation. It is fundamental for appraisal and standard control of present day. [64].

## 3. Calibration

Here is a calibration strategy for a coordinate measuring machine. It will be measuring the coordinates by using the laser tracking system. Calibration is essential in view of, for

- (1) Traceability to the length standard ought to be made sure about.
- (2) Uncertainty of estimation results can be determined.

It is essential to apprise the positioning of the four laser trackers to recognize high-accurate coordinate measurement since, supposing that the four laser trackers are organized near one another, the relationship of the assembly boundaries increments. Accuracy of the computation also diminishes. Takatsuki pointed out the essential conditions for the positioning of the laser tracker given below:

- (1) All four laser trackers ought not be in a similar plane.
- (2) Four laser trackers are prescribed to be situated at the four apices of a normal tetrahedron that covers the estimation volume. [7].

#### 4. Error compensation

Velshis et al. [17] actualized neural organizations in an error reimbursement methodology for machining with a five axis machine. The decision of a compensation procedure depends on an extraordinary degree on the kind of controller utilized or accessible on the machine, and its adaptability. In light of the past writing, a mix of calibration techniques and compensation methodologies is applied for mathematical and kinematic error remuneration to for improve the CMM. The error is calculated at different focuses in the working volume in a 3-D cross area. The calculations are finished using a basic business standard relic, and it is a ring gauge. All estimations are acted in a reference temperature and basically stable environmental conditions. The error in calculating the ring gauge diameter across, in significant axis headings, is enlisted as the nearby error of the machine estimation at the middle of the ring measure. These mistakes are coordinated for the whole machine volume to appear at the worldwide position error estimations of the entire work volume of the CMM. [5]. Error plotting is regularly sole to the CMM controller, and the precision of such a joined framework is restricted by the absence of combined laser digitizer error reimbursement. Mathematical error compensation calculations are made on a test machine at the simultaneous temperatures of 20°, 25°C and 30 °C. The CMM error reimbursement information was then used to post measure the laser digitizer directions to get improved worldwide part coordinates. At present, in any case, the exactness of such a joined framework is limited by the lack of coordinated CMM/laser digitizer mathematical error reimbursement. [16].


#### 5. Laser tracker system

So as to grow new calculations and elective verification and calibration methods petitioned to AACMM, in this work the investigation of the utilization of a laser tracker as a kind of perspective device in the calibration strategy of AACMM supplanting the regular one-dimensional measures as ball bars is introduced. The principal advancements of estimation dependent on laser tracker given to precision on examination for robot's goes back to the 1980s. Be that as it may, as of late the dimensional confirmation for enormous reach structures in automation or flight related area has thrust ahead and laser tracker innovation has become considerably throughout the most recent 25 years. The laser tracker is an enormous scope compact estimating instrument with high exactness that calculates the coordinates of an item in convex directions. It utilizes interferometry for calculating relative length and optical encoders for azimuth and height points of a beam steering mirror. A laser tracker is made out of the accompanying parts: laser source, a beam controlling function with precise encoders, interferometer, position sensor detector (PSD), pillar parting optics, a retroreflector and a control unit. These parts are utilized to follow the objective, regularly a roundly mounted retroreflector (SMR) and measure its middle x, y and z directions. [30].

#### 6. Sampling strategy

Test size is consistently related to time. It is also related to the cost and sampling procedure which we had considered; investment in time might be accomplished along with a decrease of the sample size. Besides, Sampling strategy may be beneficial to aim a decreases of the length of CMM probe paths notwithstanding diminishing the sample size for accomplishing extra time decreases. This work tried to analyse elective testing procedures with regards to exactness, number of focuses assessed and the length of the CMM probe instrument path. [2]. The sampling methodology choose assumes a critical part since it empowers to make legitimate inferences regarding measurements and kinds of a work piece. An information of the whole surface is should have been ready to determine the type of error with great exactness. When we utilizing CMM, sampling methodologies must be chosen appropriately because the discrete example that a CMM uses to quantify ought to have the option to give adequate information about the surface to choose the type of error and simultaneously decrease the review cost and time. The ideal sample size and the areas of the testing focuses which are included in the sampling procedure. Assurance of the sample size is a convoluted cycle since it is affected by various variables, for instance, the assembling cycle used, tolerance properties, error estimation strategy and certainty level of estimated results. [14].

### Touch probe



A touch trigger probe has a pointer(stylus) that is connected to a bearing plate, this is then associated with pressure sensors inside the housing of the probe. Each time the probe makes touch the work-piece, it produces an electrical signal. This signal is sent back to the CMM to make precise estimations. Another touch test having three degrees-of-opportunity power sensor is introduced. Among connections which links an acquired contact force vector and the graphical state of the probe, which is possible to conceivable the directions of the particular probe example contact focuses. In experimental model of the probe is applied to measure the coordinates of the contact points and the measure of pre travel. With the proposed probing system, the measuring error initiated by the indeterminateness of the probe-specimen contact point and the pre travel can be assessed and made up for effectively. [12].

### 7.Conclusion

Coordinate measuring machine will be proceeding with their function in supporting the creation of high precision parts in little Business and also the CMM will withal perpetuate its audit role, in particular for critical medical and aerospace firms. CMMs are too ingrained in many firms to just stop being used. We concluded the calibration system validity which is dependent upon the laser tracking system which is further an industrial utilization of the CMM, however in the market there are enormous type of CMMs which have exorbitant capacity of exact measurement. From now on, to calibrate more accurate Coordinate measuring machines, additionally distillation of the physical objects and also parts of the laser tracking interferometer prerequisite needed. In this work, an answer for the issue of non-rigid freeform inspection is appeared. By using the kinematic and geometric errors, CMM was acquired successfully with mathematical modelling. The methodology followed to arrive at the model has been clarified. For utilizing a straightforward basic antiquity, coefficients of the model were determined. Distinctive part features should be estimated least investigation time for that methodologies have been acquainted to compute sequence. The computation is very effective. A discrete measurement system such as the CMM utilizes a lot of individual points to describe a work-piece geometry. Laser tracker equipment for AACMM calibration and verification methods could be approved if the laser tracker's accuracy is ensured by means of its appropriate calibration or verification. The least complex strategies to circulate test focuses on the estimating surface are Random and Grid point appropriation techniques. The arbitrary point appropriation system arbitrarily assigns focuses on the investigation feature.

### References

[1].Aggogeri, Francesco, Giulio Barbato, Emanuele Modesto Barini, Gianfranco Genta, and Raffaello Levi. "Measurement uncertainty assessment of Coordinate Measuring Machines by simulation and planned experimentation." *CIRP Journal of Manufacturing Science and Technology* 4, no. 1 (2011): 51-56.

- [2].Carbone, V., M. Carocci, E. Savio, G. Sansoni, and L. De Chiffre. "Combination of a vision system and a coordinate measuring machine for the reverse engineering of freeform surfaces." *The International Journal of Advanced Manufacturing Technology* 17, no. 4 (2001): 263-271.
- [3].Kim, Weon-Seok, and Shivakumar Raman. "On the selection of flatness measurement points in coordinate measuring machine inspection." *International Journal of Machine Tools and Manufacture* 40, no. 3 (2000): 427-443.
- [4].Barakat, N. A., M. A. Elbestawi, and A. D. Spence. "Kinematic and geometric error compensation of a coordinate measuring machine." *International Journal of Machine Tools and Manufacture* 40, no. 6 (2000): 833-850.
- [5].Umetsu, Kenta, Ryosyu Furutani, Sonko Osawa, Toshiyuki Takatsuji, and Tomizo Kurosawa. "Geometric calibration of a coordinate measuring machine using a laser tracking system." *Measurement science and technology* 16, no. 12 (2005): 2466.
- [6].Cho, M. W., and K. Kim. "New inspection planning strategy for sculptured surfaces using coordinate measuring machine." *The International Journal of Production Research* 33, no. 2 (1995): 427-444.
- [7].Pereira, P. H., and R. J. Hocken. "Characterization and compensation of dynamic errors of a scanning coordinate measuring machine." *Precision Engineering* 31, no. 1 (2007): 22-32.
- [8].Song, C-K., and S-W. Kim. "Reverse engineering: autonomous digitization of free-formed surfaces on a CNC coordinate measuring machine." *International Journal of Machine Tools and Manufacture* 37, no. 7 (1997): 1041-1051.
- [9].Shimajima, Ken, Ryosyu Furutani, Kiyoshi Takamasu, and Kenji Araki. "The estimation method of uncertainty of articulated coordinate measuring machine." In *2002 IEEE International Conference on Industrial Technology, 2002. IEEE ICIT'02.*, vol. 1, pp. 411-415. IEEE, 2002.
- [10].Harris, J. O., and A. D. Spence. "Geometric and quasi-static thermal error compensation for a laser digitizer equipped coordinate measuring machine." *International Journal of Machine Tools and Manufacture* 44, no. 1 (2004): 65-77.
- [11].Sawano, Hiroshi, Toshimichi Gokan, Hayato Yoshioka, and Hidenori Shinno. "A newly developed STM-based coordinate measuring machine." *Precision engineering* 36, no. 4 (2012): 538-545.
- [12].Knapp, W. "Circular test for three-coordinate measuring machines and machine tools." *Precision engineering* 5, no. 3 (1983): 115-124.
- [13].Sudatham, Wiroj, Hirokazu Matsumoto, Satoru Takahashi, and Kiyoshi Takamasu. "Verification of the positioning accuracy of industrial coordinate measuring machine using optical-comb pulsed interferometer with a rough metal ball target." *Precision Engineering* 41 (2015): 63-67.
- [14].Rajamohan, G., M. S. Shunmugam, and G. L. Samuel. "Effect of probe size and measurement strategies on assessment of freeform profile deviations using coordinate measuring machine." *Measurement* 44, no. 5 (2011): 832-841.
- [15].Wu, Yongqing, Shugui Liu, and Guoxiong Zhang. "Improvement of coordinate measuring machine probing accessibility." *Precision engineering* 28, no. 1 (2004): 89-94.
- [16].Yang, Ping, Tomohiko Takamura, Satoru Takahashi, Kiyoshi Takamasu, Osamu Sato, Sonko Osawa, and Toshiyuki Takatsuji. "Development of high-precision micro-coordinate measuring machine: Multi-probe measurement system for measuring yaw and straightness motion error of XY linear stage." *Precision Engineering* 35, no. 3 (2011): 424-430.
- [17].Chen, Y. H., Y. Z. Wang, and Z. Y. Yang. "Towards a haptic virtual coordinate measuring machine." *International Journal of Machine Tools and Manufacture* 44, no. 10 (2004): 1009-1017.
- [18].Wu, Yongqing, Shugui Liu, and Guoxiong Zhang. "Improvement of coordinate measuring machine probing accessibility." *Precision engineering* 28, no. 1 (2004): 89-94.
- [19].Castro, H. F. F., and M. Burdekin. "Dynamic calibration of the positioning accuracy of machine tools and coordinate measuring machines using a laser interferometer." *International Journal of Machine Tools and Manufacture* 43, no. 9 (2003): 947-954.
- [20].Yang, Ping, Tomohiko Takamura, Satoru Takahashi, Kiyoshi Takamasu, Osamu Sato, Sonko Osawa, and Toshiyuki Takatsuji. "Development of high-precision micro-coordinate measuring machine: Multi-probe measurement system for measuring yaw and straightness motion error of XY linear stage." *Precision Engineering* 35, no. 3 (2011): 424-430.
- [21].Acero, R., A. Brau, J. Santolaria, and M. Pueo. "Verification of an articulated arm coordinate measuring machine using a laser tracker as reference equipment and an indexed metrology platform." *Measurement* 69 (2015): 52-63.
- [22].Carmignato, S., A. Voltan, and E. Savio. "Metrological performance of optical coordinate measuring machines under industrial conditions." *CIRP annals* 59, no. 1 (2010): 497-500.
- [23].Ito, So, Issei Kodama, and Wei Gao. "Development of a probing system for a micro-coordinate measuring machine by utilizing shear-force detection." *Measurement Science and Technology* 25, no. 6 (2014): 064011.
- [24].Liang, Qiaokang, Dan Zhang, Yaonan Wang, and Yunjian Ge. "Development of a touch probe based on five-dimensional force/torque transducer for coordinate measuring machine (CMM)." *Robotics and Computer-Integrated Manufacturing* 28, no. 2 (2012): 238-244.
- [25].Jeevan Kittur, M. Ramachandran, Vishal Fegade, U Ragavendran Numerical Investigation of Total Deformation in roller Bearing using Ansys Analysis, *International Journal of Mechanical and Production Engineering Research and Development*, 2018, August, 51-58.

- [26].Corrado, Andrea, and Wilma Polini. "Measurement of high flexibility components in composite material by touch probe and force sensing resistors." *Journal of Manufacturing Processes* 45 (2019): 520-531.
- [27].Wäldele, Franz, B. Bittner, K. Busch, R. Drieschner, and R. Elligsen. "Testing of coordinate measuring machine software." *Precision Engineering* 15, no. 2 (1993): 121-123.
- [28].De Nijs, J. F. C., M. G. M. Lammers, P. H. J. Schellekens, and A. C. H. Van der Wolf. "Modelling of a coordinate measuring machine for analysis of its dynamic behaviour." *CIRP Annals* 37, no. 1 (1988): 507-510.
- [29].Fan, Kuang-Chao, Fang Cheng, Weili Wang, Yejin Chen, and Jia-You Lin. "A scanning contact probe for a micro-coordinate measuring machine (CMM)." *Measurement Science and Technology* 21, no. 5 (2010): 054002.
- [30].Jackman, John, and Dong-Keun Park. "Probe orientation for coordinate measuring machine systems using design models." *Robotics and Computer-Integrated Manufacturing* 14, no. 3 (1998): 229-236.
- [31].Kruth, Jean-Pierre, Paul Vanherck, and Lieven De Jonge. "Self-calibration method and software error correction for three-dimensional coordinate measuring machines using artefact measurements." *Measurement* 14, no. 2 (1994): 157-167.
- [32].Kruth, J-P., Liang Zhou, Christophe Van Den Bergh, and Paul Vanherck. "A method for squareness error verification on a coordinate measuring machine." *The International Journal of Advanced Manufacturing Technology* 21, no. 10-11 (2003): 874-878.
- [33].Pramod Raichurkar, M. Ramachandran, V. Subramaniam, The structural and mechanical properties of the crepe-de -chine fabrics material, *International Journal of Mechanical and Production Engineering Research and Development*, 2018, December, 103-108.
- [34].Lotze, Werner. "ScanMax—a novel 3D coordinate measuring machine for the shopfloor environment." *Measurement* 18, no. 1 (1996): 17-25.
- [35].Lu, C. G., D. Morton, M. H. Wu, and P. Myler. "Genetic algorithm modelling and solution of inspection path planning on a coordinate measuring machine (CMM)." *The International Journal of Advanced Manufacturing Technology* 15, no. 6 (1999): 409-416.
- [36].Mian, Syed Hammad, and Abdulrahman Al-Ahmari. "Enhance performance of inspection process on Coordinate Measuring Machine." *Measurement* 47 (2014): 78-91.
- [37].Wozniak, Adam, and Marek Dobosz. "Factors influencing probing accuracy of a coordinate measuring machine." *IEEE Transactions on Instrumentation and Measurement* 54, no. 6 (2005): 2540-2548.
- [38].Liu, Dejun, Rensheng Che, Zifang Li, and Xiaochuan Luo. "Research on the theory and the virtual prototype of 3-DOF parallel-link coordinate-measuring machine." In *IMTC 2001. Proceedings of the 18th IEEE Instrumentation and Measurement Technology Conference. Rediscovering Measurement in the Age of Informatics (Cat. No. 01CH 37188)*, vol. 2, pp. 926-930. IEEE, 2001.
- [39].Qu, Liangsheng, Guanhua Xu, and Guohua Wang. "Optimization of the measuring path on a coordinate measuring machine using genetic algorithms." *Measurement* 23, no. 3 (1998): 159-170.
- [40].Partha Protim Das Priyank, Kumar Ghadai, M. Ramachandran, Kanak Kalita, Optimization of Turning Process Parameters by Taguchi-Based Six Sigma, *Mechanics and Mechanical Engineering*, 21(3):649-656, 2017.