



# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 01/16/2014 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Northland Gear Lube 85W140  
Product code : 50C4

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Gear Lubricant

#### 1.3. Details of the supplier of the safety data sheet

##### MANUFACTURER:

Northland Products  
1000 Rainbow Drive  
Waterloo, IA 50704

Tel: +1-319-234-5585  
+1-800-772-1724

#### 1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300  
Chemtrec (Outside USA) +1 703-527-3887 (24 hours)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
Skin Sens. 1 H317

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled

Precautionary statements (GHS-US) :

P261 - Avoid breathing dust, fume, mist, spray, vapours  
P264 - Wash hands thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing should not be allowed out of the workplace  
P280 - Wear eye protection, protective clothing, protective gloves  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CENTER/doctor/physician if you feel unwell  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362 - Take off contaminated clothing and wash before reuse  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P501 - Dispose of contents/container to comply with applicable local, national and international regulation.

#### 2.3. Other hazards

other hazards which do not result in classification :

Spills of this product present a serious slipping hazard.

# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates, petroleum, solvent-refined heavy paraffinic (IP 346<3%)	(CAS No) 64741-88-4	< 27	Acute Tox. 4 (Inhalation:dust,mist), H332
Residual oils, petroleum, solvent-refined	(CAS No) 64742-01-4	< 27	Acute Tox. 4 (Inhalation:dust,mist), H332
Polysulfides, di-tert-butyl	(CAS No) 68937-96-2	2,8 - 3,5	Skin Sens. 1B, H317
Phosphoric acid, bis(2-ethylhexyl) ester	(CAS No) 298-07-7	0,7 - 1,5	Acute Tox. 4 (Dermal), H312 Skin Corr. 1C, H314 Eye Dam. 1, H318

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest. In case of breathing difficulties administer oxygen. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. If material is injected under the skin, seek medical attention immediately. Injection under the skin of pressurized hydrocarbons can cause severe, permanent tissue damage. Get medical advice/attention.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: This product contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause an allergic skin reaction.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Precautionary measures fire	: Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Gases/vapours, toxic.
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained respiratory apparatus during longer or intensive exposition or spraying processing.
Other information	: Special danger of slipping by leaking/spilling product.

# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protective equipment as required. Special danger of slipping by leaking/spilling product. Stop leak if safe to do so. Relevant water authorities should be notified of any large spillage to water course or drain.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. Avoid breathing mist or vapor . Avoid direct eye contact with product, also via contamination on hands. Avoid contact with skin, eyes and clothes.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : The low volatility of this product does not require ventilation. However depending on the condition an adequate ventilation might be required. Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. An environmental fate analysis is not available for this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as fabric absorbents, clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Consult the appropriate authorities about waste disposal. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Special danger of slipping by leaking/spilling product.

Precautions for safe handling : Avoid contact with skin, eyes and clothes. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Empty container retains product residue. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Use only in well-ventilated areas. Take precautionary measures against static discharge. Avoid generation of dust.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation. Avoid static electricity discharges. Ground/bond container and receiving equipment. A washing facility/water for eye and skin cleaning purposes should be present.

Storage conditions : Keep out of reach of children. Keep container closed when not in use. Keep only in the original container in a cool, well-ventilated place away from highly flammable substances. Keep container tightly closed and dry.

Incompatible materials : Strong oxidizing agents.

Storage temperature : Store at ambient temperature

Heat and ignition sources : Remove all sources of ignition.

Storage area : Protect against direct sunlight.

Special rules on packaging : Correctly labelled. Do not store in unlabeled containers.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Personal protective equipment : Avoid all unnecessary exposure. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Gloves. Protective clothing. Protective goggles.



Hand protection : Wear protective gloves. Use neoprene or rubber gloves.  
Eye protection : Chemical goggles or safety glasses. with side-shields.  
Skin and body protection : If skin contact or contamination of clothing is possible, protective clothing should be worn. safety foot-wear.  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.  
Environmental exposure controls : Avoid release to the environment.  
Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Colour : Clear amber.  
Odour : Petroleum. Sulfur. Characteristic.  
Odour threshold : No data available  
pH : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : > 300 °C (> 572 °F)  
Flash point : 232 °C (450 °F)  
Self ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapour pressure : < 0,01 mm Hg Maximum @ 37.8 °C (100 °F)  
Relative vapour density at 20 °C : > 1  
Relative density : 0,906 g/cm<sup>3</sup> at 15.6 °C / 60 °F  
Solubility : Water: insoluble  
Organic solvent: completely soluble  
Log Pow : No data available  
Log Kow : Base oil hydrocarbons: log Kow > 4 (estimate)  
Viscosity, kinematic : 397 cSt @ 40°C  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidising properties : No data available  
Explosive limits : No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Hazardous polymerisation does not occur.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources. Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong oxidizing agents.

# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 10.6. Hazardous decomposition products

On burning: release of (highly) toxic gases/vapours. fume. Carbon monoxide. Carbon dioxide. Aldehydes. Hydrogen sulfide. Sulfur oxides. Nitrogen oxides (NO<sub>x</sub>). Phosphorus oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

Northland Gear Lube 85W140	
ATE (dust,mist)	1,500 mg/l/4h

Polysulfides, di-tert-butyl (68937-96-2)	
LD50 oral rat	6500 mg/kg
ATE (oral)	6500,000 mg/kg bodyweight

Phosphoric acid, bis(2-ethylhexyl) ester (298-07-7)	
LD50 oral rat	4940 µl/kg
LD50 dermal rabbit	1250 µl/kg
ATE (dermal)	1100,000 mg/kg bodyweight

Distillates, petroleum, solvent-refined heavy paraffinic (IP 346<3%) (64741-88-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	2,18 mg/l/4h
ATE (dust,mist)	2,180 mg/l/4h

Residual oils, petroleum, solvent-refined (64742-01-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	2,18 mg/l/4h
ATE (gases)	4500,000 ppmV/4h
ATE (vapours)	2,180 mg/l/4h
ATE (dust,mist)	2,180 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Based on available data, the classification criteria are not met  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
Based on available data, the classification criteria are not met  
Specific target organ toxicity (single exposure) : Not classified  
Specific target organ toxicity (repeated exposure) : Not classified  
Based on available data, the classification criteria are not met  
Aspiration hazard : Not classified  
Potential Adverse human health effects and symptoms : Harmful if inhaled.  
Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause an allergic skin reaction.  
Symptoms/injuries after skin contact : Causes skin irritation.  
Symptoms/injuries after eye contact : Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : In case of large spills the product may be hazardous to aquatic organisms due to possible formation of a film on the surface water which can diminish dissolved oxygen levels. This material contains phosphorus which is a controlled element for disposal in effluent waters in most sections of North America. Phosphorus is known to enhance the formation of algae. Severe algae growth can reduce oxygen content in the water possibly below levels necessary to support marine life.

Polysulfides, di-tert-butyl (68937-96-2)	
LC50 fishes 1	250 - 500 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Polysulfides, di-tert-butyl (68937-96-2)	
LC50 fish 2	> 1000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])
Phosphoric acid, bis(2-ethylhexyl) ester (298-07-7)	
LC50 fishes 1	20 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Distillates, petroleum, solvent-refined heavy paraffinic (IP 346<3%) (64741-88-4)	
LC50 fishes 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Residual oils, petroleum, solvent-refined (64742-01-4)	
LC50 fishes 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and degradability

Northland Gear Lube 85W140	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

Northland Gear Lube 85W140	
Log Kow	Base oil hydrocarbons: log Kow > 4 (estimate)
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Liquid product may not be disposed of with household waste or landfilled. Do not allow to enter into drains/waters or in the soil. Dispose of contents/container to comply with applicable local, national and international regulations. Used oil, may contain harmful impurities. It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

Not applicable

### 14.2. UN proper shipping name

Not applicable

### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Polysulfides, di-tert-butyl (68937-96-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Phosphoric acid, bis(2-ethylhexyl) ester (298-07-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Distillates, petroleum, solvent-refined heavy paraffinic (IP 346<3%) (64741-88-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### Residual oils, petroleum, solvent-refined (64742-01-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

### CANADA

#### Polysulfides, di-tert-butyl (68937-96-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Phosphoric acid, bis(2-ethylhexyl) ester (298-07-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Distillates, petroleum, solvent-refined heavy paraffinic (IP 346<3%) (64741-88-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Residual oils, petroleum, solvent-refined (64742-01-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

### EU-Regulations

#### Polysulfides, di-tert-butyl (68937-96-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### Phosphoric acid, bis(2-ethylhexyl) ester (298-07-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### Distillates, petroleum, solvent-refined heavy paraffinic (IP 346<3%) (64741-88-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### Residual oils, petroleum, solvent-refined (64742-01-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Skin Sens. 1 H317  
Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

### Classification according to Directive 67/548/EEC or 1999/45/EC

Xi; R36/38  
R43  
N ; R51/53

Full text of R-phrases: see section 16

### 15.2.2. National regulations

#### Polysulfides, di-tert-butyl (68937-96-2)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

#### Phosphoric acid, bis(2-ethylhexyl) ester (298-07-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on the Canadian Ingredient Disclosure List

# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### Distillates, petroleum, solvent-refined heavy paraffinic (IP 346<3%) (64741-88-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

### Residual oils, petroleum, solvent-refined (64742-01-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

### 15.3. US State regulations

#### Polysulfides, di-tert-butyl (68937-96-2)

U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

#### Phosphoric acid, bis(2-ethylhexyl) ester (298-07-7)

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

#### Distillates, petroleum, solvent-refined heavy paraffinic (IP 346<3%) (64741-88-4)

U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

#### Residual oils, petroleum, solvent-refined (64742-01-4)

U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

## SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
Skin Sens. 1B	Sensitisation — Skin, category 1B
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H411	Toxic to aquatic life with long lasting effects
R36/38	Irritating to eyes and skin



# Northland Gear Lube 85W140

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
N	Dangerous for the environment
Xi	Irritant

SDS US (GHS HazCom 2012)

*The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Northland Products Company's knowledge; however, Northland Products Company makes no warranty whatsoever, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Northland Products Company assumes no responsibility for the injury to the recipient or to third party persons or for any damage to any property and recipient assumes all such risks*