



Northland Pride EP I Extreme Duty Grease

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 04/06/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Trade name : Pride EP I Extreme Duty Grease
Product code : 85G0
Other means of identification : Lubricating Grease

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricating Grease

1.3. Details of the supplier of the safety data sheet

MANUFACTURER:

Northland Products
1000 Rainbow Drive
Waterloo, IA 50704

Tel: +1-319-234-5585
+1-800-772-1724

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300
Chemtrec (Outside USA) +1 703-527-3887 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

other hazards which do not result in classification : This product contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Injection under skin can cause severe injury. Most damage occurs in the first few hours. Initial symptoms may be minimal.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name : Northland Pride EP I Extreme Duty Grease

Full text of H-phrases: see section 16

3.2. Mixture

This product does not contain any substance presented in above cut-off concentration limits that classified as hazardous in accordance with paragraph (d) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Injection of petroleum hydrocarbons requires immediate medical attention.

First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest. In case of breathing difficulties administer oxygen. In all cases of doubt, or when symptoms persist, seek medical advice.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

Northland Pride EP I Extreme Duty Grease

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

- First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. If redness, burning, blurred vision or swelling occur, transport to nearest medical facility for additional treatment.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : This product contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects.
- Symptoms/injuries after inhalation : In the event of insufficient ventilation: May produce an allergic reaction.
- Symptoms/injuries after skin contact : Frequent or prolonged contact with skin may cause dermal irritation.
- Symptoms/injuries after eye contact : Oil Mist. May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : When heated above the flash point, releases flammable vapours.

5.3. Advice for firefighters

- Precautionary measures fire : Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Gases/vapours, toxic.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained respiratory apparatus during longer or intensive exposition or spraying processing.
- Other information : Special danger of slipping by leaking/spilling product.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protective equipment as required. Special danger of slipping by leaking/spilling product. Stop leak if safe to do so. Relevant water authorities should be notified of any large spillage to water course or drain.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : The low volatility of this product does not require ventilation. However depending on the condition an adequate ventilation might be required.

6.2. Environmental precautions

Prevent entry to sewers and public waters. An environmental fate analysis is not available for this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as fabric absorbents, clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Consult the appropriate authorities about waste disposal. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Special danger of slipping by leaking/spilling product.

Northland Pride EP I Extreme Duty Grease

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

- Precautions for safe handling : Avoid contact with skin, eyes and clothes. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Empty container retains product residue. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Proper grounding procedures to avoid static electricity should be followed.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Discard contaminated leather articles.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use. Keep only in the original container in a cool, well-ventilated place away from highly flammable substances. Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed.
- Incompatible materials : Strong acid. Base. Oxidizing agents.
- Storage temperature : Store at ambient temperature
- Heat and ignition sources : Remove all sources of ignition.
- Storage area : Protect against direct sunlight.
- Special rules on packaging : Correctly labelled.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbonic acid calcium salt (471-34-1)		
USA OSHA	OSHA PEL (TWA) (mg/m ³) : Respirable fraction	5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³) : Total dust	15 mg/m ³

8.2. Exposure controls

- Appropriate engineering controls : A washing facility/water for eye and skin cleaning purposes should be present. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits.
- Personal protective equipment : Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Avoid all unnecessary exposure. The following pictograms represent the minimum requirements for personal protective equipment. Gloves. Protective clothing. Protective goggles.



- Hand protection : Wear protective gloves, rubber gloves.
- Eye protection : Chemical goggles or safety glasses. with side-shields.
- Skin and body protection : Chemical resistant suit. Wear rubber boots.
- Respiratory protection : Work in well-ventilated zones or use proper respiratory protection.
- Thermal hazard protection : In case of insufficient ventilation, wear suitable respiratory equipment. Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). Wear heat resistant boots and protective clothing when handling material at elevated temperatures.
- Environmental exposure controls : Do not allow run-off from fire-fighting to enter drains or water courses. Ensure waste is collected and contained. Notify authorities if product enters sewers or public waters.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Solid, Tacky
- Colour : Purple.
- odour : Petroleum. characteristic.
- Odour threshold : No data available
- pH : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available

Northland Pride EP I Extreme Duty Grease

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Flash point	: >200 °C (392 °F)
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: < 1 mm Hg Maximum @ 37.8 °C (100 °F)
Relative vapour density at 20 °C	: > 1
Relative density	: 0.873 g/cm ³ at 15.6 °C / 60 °F
Solubility	: Water: insoluble Organic solvent: completely soluble
Log Pow	: Base oil hydrocarbons: log Kow > 4 (estimate)
Log Kow	: Base oil hydrocarbons: log Kow > 4 (estimate)
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
NLGI Grade	: 1

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable at normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources.

10.5. Incompatible materials

Strong acid. Strong bases. Oxidizing agents.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Carbonic acid calcium salt (471-34-1)

LD50 oral rat	6450 mg/kg
---------------	------------

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classifiedBased on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classifiedBased on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classifiedBased on available data, the classification criteria are not met
Aspiration hazard	: Not classifiedMay be fatal if swallowed and enters airways
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: In the event of insufficient ventilation: May produce an allergic reaction.
Symptoms/injuries after skin contact	: Frequent or prolonged contact with skin may cause dermal irritation.
Symptoms/injuries after eye contact	: Oil Mist. May cause eye irritation.

Northland Pride EP I Extreme Duty Grease

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : An environmental fate analysis is not available for this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

Carbonic acid calcium salt (471-34-1)

LC50 fishes 1	56000 mg/l (Exposure time: 96 h - Species: Gambusia affinis – Adult [Fresh water])
---------------	--

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Product may not be disposed of with household waste or landfilled. Do not allow to enter into drains/waters or in the soil.

Additional information : Used oil/grease, may contain harmful impurities. It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Northland Pride EP I Extreme Duty Grease	
SARA Section 311/312 Hazard Classes	This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802
Clean Water Act (CWA) 311	Maleic anhydride; Naphthalene
Clean Water Act (CWA) 307	Zinc compounds; Antimony compounds; zinc oxide; Naphthalene

Northland Pride EP I Extreme Duty Grease

All Components listed on the United States TSCA (Toxic Substances Control Act) inventory

Northland Pride EP I Extreme Duty Grease

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

15.2. International regulations

CANADA

Northland Pride EP I Extreme Duty Grease

All components listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Northland Pride EP I Extreme Duty Grease

All Components listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

Northland Pride EP I Extreme Duty Grease

All Components listed on the AICS (the Australian Inventory of Chemical Substances)
All Components listed on Inventory of Existing Chemical Substances (IECSC)
All Components listed on the Korean ECL (Existing Chemical List) inventory.
All Components listed on New Zealand - Inventory of Chemicals (NZIoC)
All Components listed on Inventory of Chemicals and Chemical Substances (PICCS)

15.3. US State regulations

*Prop 65 – Contains Naphthalene

SECTION 16: Other information

Other information : None.

SDS US (GHS HazCom 2012)

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Northland Products Company's knowledge; however, Northland Products Company makes no warranty whatsoever, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Northland Products Company assumes no responsibility for the injury to the recipient or to third party persons or for any damage to any property and recipient assumes all such risks