

Premium Hydraulic Oils

Features & Benefits

- Does Not Emulsify With the Machine Coolants
- Excellent Metal Wetting & Adhesiveness
- Superior Lubrication & EP Characteristics
- Eliminates Chatter & Scoring
- Meets Vickers, Cincinnati, & Dension Requirements
- Excellent Thermal Stability

AW 32 46 68

PRODUCT DESCRIPTION

Ashburn PREMIUM HYDRAULIC OILS are available in three primary ISO Grades and contain superior anti wear additives. These products are thermally stable, resist sludge formation, and are chemically stable. Separate quickly from water and will not contribute to the formation of metal-etching acids or corrosives. Inhibited against rust in both fresh and salt water.



Recommended for service in vane, piston, and gear pumps when used in accordance with manufacturer's recommendation. These oils are designed to provide maximum service life to these pumps and other circuit components such as motors and servos.

PACKAGING

32	F-8322-14	1 GALLON
32	F-8323-05	5 GALLON
32	F-8324-55	55 GALLON
32	F-8324-275	275 GALLON
46	F-8462-14	1 GALLON
46	F-8463-05	5 GALLON
46	F-8464-55	55 GALLON
46	F-8464-275	275 GALLON
68	F-8682-14	1 GALLON
68	F-8683-05	5 GALLON
68	F-8684-55	55 GALLON
68	F-8684-275	275 GALLON

TYPICAL ANALYSIS

	AW 32	AW 46	AW 68
GRAVITY, API:.....	31.6	30.3	29.6
POUNDS PER GALLON:.....	7.21	7.26	7.32
FLASH POINT (°F):.....	420	445	465
VISCOSITY, CST at 40 C:.....	28.5 - 35.2	41.4 - 50.6	61.2 - 74.8
VISCOSITY, SUS at 100 F:.....	155	225	330
POUR POINT (°F):.....	-20	-15	10
ISO VG NUMBER:.....	32	46	68