

CWS-LP Water Softener

Fleck 5600 Econominder Control Valve

These top quality control valves are available in 24V or 110V. The regeneration cycles are automatic and dependable. Valve body and meter module are molded from glass-reinforced Noryl for exceptional strength and durability.



The CWS Low Profile Brine Cabinet

Features a stylistic design easily accessible integrated safety brine valve, easy access lift-off salt lid with a 200lb salt holding capacity.

Limited Lifetime Warranty

On pressure tanks and brine tanks, and a full 3 year warranty on parts (Control valve & brine tank internals).

Locally Manufactured by:

Domestically Manufactured
From NSF certified components at our facilities in
Tucson, AZ and Las Vegas NV

Proven Reliability

THOUSANDS are in service in western United States

Over 50 Year Reputation

Of immaculate customer service satisfaction, integrity and quality!

Poly Glass Tanks

Tanks constructed of a high-density polyethylene inner shell, thermal wound with fiberglass. These tanks are completely non-corrosive!

**MADE IN
USA**

Specifications

MODEL	SOFTENING CAPACITY	PRESSURE TANK SIZE	POUNDS OF SALT PER REGEN	GALLONS OF WATER USED PER REGEN*	FLOW RATE
WS-56M-1035CWS-LP	22,000	10X35	10	35-50*	19
	32,000	10X35	18	60-90*	19

*Depending on local water conditions

SYSTEM INCLUDES A BYPASS VALVE

**3/4", 1" Stainless Steel FNPT Bypass
SOLD SEPARATELY**

OPERATING PRESSURE IS 40 - 90 PSI @ 34F - 110F

Authorized Distributor: