








LOW VOLTAGE POWER SUPPLIES

Note: Tempo reserves the right to change or modify driver specifications and/or manufacturer without notification either due to inventory availability from third party vendors or as part of the company's continuing product improvement program.

12v Output Drivers				
Catalog Number	Description	Mfg	Mfg Part Number	Dimensions
PWR-120-EL-040-T 	120V AC Input, 12V DC Output, 40W, Triac Dimming (to 1%)	Lutron	LTEA4U1UKN-AV120	3.00" (76 mm) W 1.00" (25 mm) H 4.90" (124 mm) L
PWR-120-EL-040-T-1 	120V AC Input, 12V DC Output, 40W, Triac Dimming (to 1%)	Lutron	LTEA4U1UMN-AV120	1.18" (30 mm) W 1.00" (25 mm) H 14.25" (362 mm) L
PWR-UNV-EL-060 	120-277V AC Input, 12V DC Output, 60W, Non-Dimming	Fulham	T1120012V-60LE	1.69" (43.0 mm) W 1.22" (31.0 mm) H 8.32" (211.4 mm) L
PWR-UNV-EL-060-Z 	120-277V AC Input, 12V DC Output, 60W, 0-10V Dimming (to <10%)	Fulham	T1M1UNV012V-60L	1.69" (43.0 mm) W 1.22" (31.0 mm) H 8.32" (211.4 mm) L
12v Output Transformers				
PWR-T010012/2 	120V AC Input, 12V AC Output, 100W, 2 Circuit, Class II Magnetic, NEMA 3R Case	Sebco	1107	6.75" (171mm) H 5.0" (127mm) W 4.5" (114mm) D
PWR-T015012/2 	120V AC Input, 12V AC Output, 150W, 3 Circuit, Class II Magnetic, NEMA 3R Case	Sebco	1108	6.75" (171mm) H 5.0" (127mm) W 4.5" (114mm) D
PWR-T025012/2 	120V AC Input, 12V AC Output, 250W, 4 Circuit, Class II Magnetic, NEMA 3R Case	Sebco	1109	6.75" (171mm) H 5.0" (127mm) W 4.5" (114mm) D



LOW VOLTAGE POWER SUPPLIES

Note: Tempo reserves the right to change or modify driver specifications and/or manufacturer without notification either due to inventory availability from third party vendors or as part of the company's continuing product improvement program.

24v Output Drivers				
Catalog Number	Description	Mfg	Mfg Part Number	Dimensions
PWR-120-EM-040-T 	120V AC Input, 24V DC Output, 40W, Triac Dimming (to 1%)	Lutron	LTEA4U1UKN-CV240	3.00" (76 mm) W 1.00" (25 mm) H 4.90" (124 mm) L
PWR-120-EM-040-T-1 	120V AC Input, 24V DC Output, 40W, Triac Dimming (to 1%)	Lutron	LTEA4U1UMN-CV240	1.18" (30 mm) W 1.00" (25 mm) H 14.25" (362 mm) L
PWR-UNV-EM-060 	120-277V AC Input, 24V DC Output, 60W, Non-Dimming	Fulham	T1UNV024V-60L	1.70" (43mm) W 1.21" (31mm) H 9.49" (241mm) L
PWR-UNV-EM-060-A 	120-277V AC Input, 24V DC Output, 60W, Dimmable 1~10VDC or PWM	Meanwell	LPF-60D-24	1.69" (43mm) W 1.26" (32mm) H 6.4" (162.5mm) L
PWR-UNV-EM-060-Z 	120-277V AC Input, 24V DC Output, 60W, 0-10V Dimming (to <10%)	Fulham	T1M1UNV024V-60L	1.69" (43mm) W 1.22" (31 mm) H 9.49" (241 mm) L
PWR-UNV-EM-100 	120-277V AC Input, 24V DC Output, 100W, Non-Dimming	Fulham	T1UNV024V-100LE	1.69" (43mm) W 1.22" (31mm) H 9.49" (241mm) L
PWR-UNV-EM-100-Z 	120-277V AC Input, 24V DC Output, 100W, 0-10V Dimming (to <1%)	EPT	DBFE-100U402-00	2.3" (58mm) W 1.22" (31mm) H 7.5" (190mm) L

LOW VOLTAGE POWER SUPPLIES

Note: Tempo reserves the right to change or modify driver specifications and/or manufacturer without notification either due to inventory availability from third party vendors or as part of the company's continuing product improvement program.

DMX/RDM 24v Output Drivers				
Catalog Number	Description	Mfg	Mfg Part Number	Dimensions
PWR-UNV-EM-100-N 	120-277V AC Input, 24V DC Output, 100W, DMX/RDM	Fulham	T4N4UNV024V-100B	3.17" (81mm) W 1.20" (30mm) H 9.08" (229mm) L
PWR-UNV-EM-100-N-1 	120-277V AC Input, 24V DC Output, 100W, DMX/RDM	Fulham	T4N4UNV024V-100K	1.62" (41mm) W 1.19" (30mm) H 14.56" (370mm) L