

# **Pana Tri-County Fair Demo Derby**

## **2018 BONE STOCK RULES**

**New Rules in Red**

### **Participant Regulations**

Bone stock class is open to all men and women 15 and over. If under the age of 18 you must have a notarized permit signed by a parent/guardian. Driver may move forward or backward. Driver must make contact every 60 seconds or be disqualified. No sandbagging. If you sandbag the race will be stopped and a sandbagger flag will be put on top of your car. You must show visible damage or must move when hit.

### **Preparation of Cars**

This class will be limited to 1980 or newer cars. All glass, chrome, pot metal, carpet, headlights, tail lights and back seat must be removed. Anything flammable must be removed before reaching exhibit area.

### **Mandatory Must**

have number on both front doors and on roof. Must be big enough and bright enough to read. Use your choice of number. No Profanity.

**THE RULES BELOW ARE THE ABSOLUTE MAX YOU MAY DO TO A CAR**

1. Stock gas tank can be used under car if it is in front of the rear axel. If changed to inside it must be a metal fuel cell no exceptions. Must be secured properly to the floor or bolted to the cage, but not both. No fuel leakage. No more than 6 gallons of gas.
2. Battery may be relocated to inside of car but must be secured properly (1 automotive battery)
3. Hood must have a 5x5 hole cut in it to extinguish fires. Hood must open for inspection and must remain on hinges. You can use 8 pieces of chain 3/8. 6 in hood to fender and 2 from hood to bumper or you can use 9 wire the same way with 3 wraps per fastening spot. Must have windshield bar from top of windshield to top of firewall. You can use 9 wire, chain or 3 inch flat metal. 2 max in this area
4. Trunks must be on hinges. You can use 8 pieces of chain 3/8 in trunk. 6 to fasten trunk lid and 2 from trunk lid to bumper. Or you can use 9 wire the same way with 3 wraps per fastening spot. You may tuck 50% of trunk lid only or remove lid completely. No body creasing of any kind. No sedagons.
5. Doors you can use 6 pieces of chain 3/8 per door or 6 pieces of 9 wire per door with 3 wraps. You may have a 4 post cage with 2 side bars and 2 cross bars. The cage cannot extend past dash area in front and no farther than 6 inches behind driver's door. This can be welded or bolted in. No down tubes. This is for driver's safety only. Not intended for reinforcement. If cage is too big you will be asked to cut. May also have a halo bar.
6. TIRES: D.O.T. approved light truck tires max.
7. REARENDS: Locking of rearend is permitted.
8. FRAME: Notching of frame is permitted.
9. BUMPERS: Must be stock bumper or 80's or newer stock bumper. Can be bolted on with two 3/4 x 8 inch althred with 3 inch washer. Can also use 9 wire or chain along with bolting.
10. THIS IS THE MAX OF WHAT YOU CAN DO ON A BONE STOCK CAR. DO NOT DO ANYMORE THAN THIS OR YOU WONT BE RUNNING THIS CLASS.
11. Engine must be GM to GM, Ford to Ford, Chrysler to Chrysler. May have headers.
12. SHIFTER. May use a single push pull rod.