

Job Name:

Schedule Reference:

Date:



GENERAL FEATURES

- Dual set point functionality
- Lightweight and compact design
- Four-speed fan settings
- Built-in condensate lift mechanism
- Ventilation air intake supported

OPTIONS

- CN24 Relay Kit.....CN24RELAY-KIT-CM3

* Cooling / Heating capacity indicated at the maximum value at operation under the following conditions:
 Cooling | Indoor: 80° F (27° C) DB / 67° F (19° C) WB
 Cooling | Outdoor: 95° F (35° C) DB
 Heating | Indoor: 70° F (21° C) DB
 Heating | Outdoor: 47° F (8° C) DB / 43° F (6° C) WB

SPECIFICATIONS

Capacity*

Cooling12,000 Btu/h
 Heating13,500 Btu/h

Power

Power Source208 / 230V, 1 phase, 60Hz

Power Consumption

Cooling 0.04 kW
 Heating 0.04 kW

Current

Cooling 0.21 A
 Heating 0.21 A
 Minimum Circuit Ampacity (MCA)0.26 A
 Maximum Overcurrent Protection (MOCP)15 A

External Finish

.....Grille: 6.4Y 8.9/0.4

Dimensions

Inches9-1/16" h x 31-31/32" w x 15-9/16" d
 mm230 h x 812 w x 395 d
 Grille
 Inches1-3/16" h x 39-3/8" w x 18-17/32" d
 mm30 h x 1000 w x 470 d

Net Weight

Unit31 lb / 14 kg
 Grille7 lb / 3 kg

Coil Type

.....Cross fin

Fan

Type x QuantityLine flow fan x 1
 Airflow Rate (Low-Mid1-Mid2-High) .. 258-283-304-328 CFM
 Motor Type DC brushless motor

Air Filter

.....PP honeycomb

Refrigerant Pipe Dimensions

Liquid1/4" / 6.35 mm flare
 Gas1/2" / 12.7 mm flare

Drainpipe Dimension

.....O.D. 1" / 26 mm

Sound Level

(Low-Mid1-Mid2-High)32-34-36-37 dB (A)

Notes:



