

# RIG #7E EQUIPMENT

SCR:	Diesel Electric
PRIME MOVERS:	(4) Generators
TOP DRIVE:	500 Ton Tesco ECI900
PRESSURE RATING:	7 500 Psi
DEPTH CAPACITY:	6 500 m

## Mast

Make:	Dreco
Model:	DAM14225-1330
Type:	Cantilever
Hook Load:	448,800 daN w/12 lines
Clear Height:	43.30 m
Base Width:	7.62 m

## Substructure

Make:	Dreco
Type:	Box on Box on Box
Casing Capacity:	400,000 daN
Setback Capacity:	222,400 daN
KB to Ground:	8.96 m
Clear Height:	7.62 m

## Drawworks

Make:	Oilwell Modified 840
Rating:	(1 394 HP) 1 040 kw
Powered By:	GE752HT

## Mud Pumps (2)

Make:	L.G.F.
Model:	RSF1600
Powered By:	(2) per pump. GE752
Power Rating:	(1 000 HP) 746 kw

## Mud Tanks

Compartments:	6
Volume:	215 m <sup>3</sup>

## Premix Tank

Volume:	87 m <sup>3</sup>
---------	-------------------

## Shale Shakers (2)

Make:	Swaco Mongoose PT
-------	-------------------

## Block

Make:	Oilwell 6-60-H500
Rating:	445,000 daN



## Top Drive

Make:	Tesco ECI900
Rating:	500 Tons

## Preventer Stack

Size:	346 mm
Rating:	70,000 kPa

## Engines (3)

Make:	Caterpillar
Model:	3512B
Generator Size:	1 225 kw

## Engines (1)

Make:	Caterpillar
Model:	3508 Bi-Fuel
Generator Size:	1 050 kw

## Boiler

Make:	Volcano - 125 HP
Type:	Bi-Fuel

ALL SPECIFICATIONS ARE RATED AT 100%