



**APPLY SOME SERIOUS STICKING POWER.
AND TACKLE THE EXTREME CONDITIONS.**

FLASHING ALL-TEMPERATURE



Install the system. Get a lifetime limited warranty.*
TYPAR® All-Temperature Flashing, along with the full TYPAR®
Weather Protection System delivers unbeatable coverage.

*Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.



TYPAR® ALL-TEMPERATURE FLASHING

WHEN WE SAY MAXIMUM ADHESION, WE MEAN IT.

Bitter cold. Searing heat. They won't compromise your ability to get the strongest seal possible. TYPAR All-Temperature Flashing is engineered to perform in a broad range of extremes and protect against moisture penetration at windows, doors and thru-wall entry points. Whether we're talking OSB, plywood, aluminum, vinyl, or the building wrap, it sticks tight under the toughest conditions. Its easy-to-install properties make it ideal for faster, hassle-free installation during construction. And its durable character defends homes for years after the cladding is up.

LEADING FEATURES AND BENEFITS:

- Suitable for installation down to 0° F (-18° C)
- Thermally stable up to 180° F (82° C)
- Sticks to wet surfaces
- Self-seals around nail penetrations
- Split poly backing for easy install
- No primer required
- No VOC, NFCC, or CFC
- Two-year shelf life
- Lifetime limited warranty*

INSTALL THE SYSTEM. GET A LIFETIME LIMITED WARRANTY:

TYPAR All-Temperature Flashing, Building Wraps, and Construction Tape make up the complete TYPAR® Weather Protection System. It's the only lineup with superior air and water holdout, exceptional tear strength, optimal breathability, and this: lifetime limited warranty coverage.*

*TYPAR All-Temperature Flashing is part of the TYPAR® Lifetime Limited System Warranty when used with the complete TYPAR Weather Protection System. Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **we make no warranties, express or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads, subject to the limitations and exclusions described therein.**

TYPICAL CHARACTERISTICS:

Adhesive	Block copolymer
90 Peel Adhesion	
Plywood	5.0 lb/in
OSB	3.8 lb/in
Facer	4.6 lb/in
Mold Growth (ASTM G21)	No growth
Application Temp	0°F (-18°C) to 180°F (82°C)
Nail Sealability (AAMA 711-13)	PASS
UV Stability	6 months

ROLL SIZES:

4" x 75'	6" x 75'	9" x 75'
12" x 75'		



Made in USA. © 2017, Berry Plastics Corporation. TYPAR® is a registered trademark of Fiberweb, LLC, a wholly owned subsidiary of Berry Plastics Corporation. Please visit TYPAR.com for installation instructions and warranty information. Building Wraps | Flashings | Construction Tape

