

# WINDOW FILM PERFORMANCE DATA



	% Visible Light Transmission	% Total Solar Energy Rejection	% IR Energy Rejection (IRER)*	% Selective IR Rejection (SIRR)**	% Ultraviolet Protection (wavelengths 300-380nm)	% Glare Reduction	% Visible Light Reflection
--	------------------------------	--------------------------------	-------------------------------	-----------------------------------	--	-------------------	----------------------------

CLASSIC™ SERIES		Good heat rejection and enhanced style						
Classic 05	5	44	22	29	>99	94	5	
Classic 15	18	40	22	29	>99	79	5	
Classic 30	33	36	22	29	>99	63	6	
Classic 35	38	35	22	29	>99	57	6	
Classic 50	60	28	22	29	>99	32	7	
PINNACLE® SERIES		Superior heat rejection and enhanced style with no signal interference						
Pinnacle 05	5	64	62	90	>99	94	5	
Pinnacle 15	19	60	62	89	>99	78	5	
Pinnacle 30	33	56	61	88	>99	63	6	
Pinnacle 35	38	55	61	88	>99	57	6	
Pinnacle 40	43	53	61	88	>99	51	6	
Pinnacle 50	55	50	61	88	>99	38	7	
STRATOS™ SERIES		Most advanced Hybrid-Matrix™ nano-ceramic technology for maximum heat rejection and enhanced style with no signal interference						
Stratos 15	17	63	66	95	>99	80	5	
Stratos 30	32	59	66	96	>99	63	6	
Stratos 35	39	58	67	97	>99	56	6	
Stratos 40	43	57	66	96	>99	52	6	
Stratos 50	56	54	67	97	>99	37	7	
Stratos 70	69	49	66	96	>99	21	8	

**EASTMAN**

LLumar.com

\*IRER is a more complete measurement of heat experienced from solar infrared radiation (780-2500nm) including absorbed and re-radiated energy. \*\*SIRR is a measurement of solar infrared radiation (780-2500nm) not directly transmitted through glass. Data captured using NFRC guidelines and calculated for single pane, 1/4" clear glass. Reported values are taken from representative product samples and are subject to normal manufacturing variances. Actual performance will vary based on a number of factors, including glass type and properties. See LLumar.com for technical data. © 2017 Eastman Chemical Company. FormulaOne®, the FormulaOne® logo, LLumar® and the LLumar® logo are trademarks of Eastman Chemical Company or one of its wholly owned subsidiaries. As used herein, ® denotes registered trademark status in the U.S. or other countries.

