

Dual Channel 3Gbit SDI to Fiber Transmitter

- Dual channel
- Supports SDI video inputs up to 3Gbit/s (1080p60)
- 3Gbit Level A and Level B support (all formats)
- Auto reclocking 270Mbit / 1.48Gbit / 2.97Gbit
- Error free optical transmission
- Up to 10km (6.2 miles) @ 3Gbit/s
- Duplex LC/PC singlemode optical connection
- Supports hot swapping and hot plugging

The OTT 1812 is a compact dual channel SDI to fiber optic transmitter designed to combat the restrictions involved with the distribution of uncompressed broadcast quality video signals over long distances.

When paired with the dual channel fiber optic to SDI receiver (e.g. yellobrik ORR 1802) you have a very cost effective dual channel optical transmission / receiver system for signals up to 1080p60 (3Gbit/s), while preserving full uncompressed quality.

The OTT 1812 has two completely independent channels and each will auto-detect and re-clock any 270Mbit / 1.48Gbit and 2.97Gbit SDI source prior to optical transmission. The module is fully compatible with 3Gbit Level A and Level B formats.




Technical Specifications


Input	2 x SDI video on 75 Ohm BNC connector (two independent channels)
	SMPTE 424M, SMPTE 292M, SMPTE 259M, DVB-ASI
	Multi-standard operation from 270Mbit/s to 3Gbit/s
	Multi-rate reclocking 270Mbit/s - 1.48Gbit/s - 2.97Gbit/s
	Return Loss: > 15dB to 1.5GHz and > 10dB up to 3GHz
	Automatic cable EQ (Belden 1694A cable) 250m @ 270Mbit/s, 140m @ 1.5Gbit/s, 80m @ 3Gbit/s
Optical Outputs	2 x fiber optic outputs (one for each channel) Duplex (single mode) using LC/PC Connections
	SMPTE 297M - 2006
	Wavelength 1310nm (each channel)
	Optical power -5dBm (each channel)
	TX active LEDs on side of module
	Max. distance approx. 10km (6.2 miles) @ 3Gbit/s (Singlemode)
Power	+12VDC @ 2.5W nominal - (supports 7 - 16VDC input range)
Physical	Size: 140mm x 42mm x 22mm (5.51" x 1.65" x 0.86") including connectors Weight: 125g (4.4oz)
Ambient	5 - 40°C (41 - 104°F) 90% Humidity (non condensing)
Model #	OTT 1812 - (EAN# 4250479318229)
Includes	Module, AC power supply, transport case

Fiber Adapter Options

These adapter kits allow the use of ST or SC fiber connections on the module. SMF 0.5m (19.6") tail introduces less than 0.25dB attenuation.



Model# **LC/SC DUP**
LC/PC to SC/PC Adapter



Model# **LC/ST DUP**
LC/PC to ST/SC Adapter

Power Adapter Options

The kit **INCLUDES** AC power supply. The power adapters below are optional.



P-TAP 1000
Use with a standard battery P-TAP power source.



XLR 1000
Use with a standard 4 pin XLR camera battery power source.

Specifications subject to change