

BR-6120 Series

LED Architectural Bollard

Type:

Catalog Number:

Project/Location:

Approved By:

SPECIFICATIONS

Housing: Heavy-duty construction of corrosion resistant extruded aluminum. Stainless steel hardware.

Gasket: Closed cell silicone foam gasket. Seals out moisture, dust, and insects for weather-tight operation.

Mounting: Secures with 3/4" x 17" galvanized anchor bolts.

Lens: 1/8" thick UV stabilized high impact 2447 white acrylic with *optional* 360° perforated shield (PS).

Dim: 0-10V.

Driver: Constant current and Universal input voltage 120-277V, 50-60Hz line voltage frequency. Operating temperature -20°C to 40°C, Power Factor $\geq .90$.

LED: 3000 (30K).

Lumens: 5525, CRI: 80.

Finish/Colors: Zinc based primer with polyester powder coat finish in Matte Black (MB), Matte White (MW), Matte Bronze (BZ), Silver Gray (SG), or a custom color (CC).

Testing: LM79, LM80, ETL.

Conforms to UL Standard 1598. Suitable for wet locations.

See options page for additional information or consult factory.



EMERGENCY BATTERY
BACKUP AVAILABLE


Series	Source	Wattage/Max
BR-6120	LED	60W

ORDERING EXAMPLE

BR-6120 – 60WLED – 30K – UNV – XX – DIM



Shown with perforated pattern shield option.



ELCAST LIGHTING

815 S. Kay Ave., Addison, IL 60101 USA • 630.543.5390
www.ElcastLtg.com • ElcastLtg@ElcastLtg.com

Made in USA – 5 year limited warranty

©2017. Specifications are subject to change without notice. Consult factory for verification.

REV 10-19