

# 1800-CM Series

## LED Architectural Down Cylinder / Ceiling Mount

Type:

Catalog Number:

Project/Location:

Approved By:

### SPECIFICATIONS

**Housing:** Heavy-duty construction of corrosion resistant extruded aluminum. Stainless steel hardware.

**Gasket:** Closed cell silicone foam gasket. Seals out moisture, dust, and insects for weather-tight operation.

**Mounting:** Ceiling mount over standard J-box.

**Lens:** 1/8" thick clear tempered glass.

**Driver:** Constant current and Universal input voltage 120-277V, 50-60Hz line voltage frequency. Operating temperature -20°C to 40°C, Power Factor  $\geq$  .90.

**LED:** Specify amber (A), blue (B), green (G), red (R), or 3000 (30K), 3500 (35K), 4000 (40K), and 5000K (50K). 40K Standard.

**Lumens:** 3100.

**Finish/Colors:** Zinc based primer with polyester powder coat finish in Matte Black (MB), Matte White (MW), Matte Bronze (BZ), Silver Gray (SG), or a custom color (CC).

**Testing:** LM79, LM80, ETL.  
Conforms to UL Standard 1598. Suitable for wet locations.

### Options:

BR Black baffle regressed lens  
FLA Harsh environment finish  
TF Turtle Friendly 590 nm Amber LED

Down Light available in 6" or 8" DIA.


*Down Light, Ceiling or Pendant Mounts available in various sizes.  
See options page for additional information or consult factory.*



Series	Source	Wattage/Max
1800-CM	LED	28W

### ORDERING EXAMPLE

1800-CM – 28WLED – 40K – 120 – MB



## ELCAST LIGHTING

815 S. Kay Ave., Addison, IL 60101 USA • 630.543.5390  
www.ElcastLtg.com • ElcastLtg@ElcastLtg.com

**Made in USA** – 5 year limited warranty

©2017. Specifications are subject to change without notice. Consult factory for verification.