

BatesField GPU - Hangar Powered

DC OUTPUT POWER: Standard with 28VDC outlet with 12VDC available for \$150.
Capable of **2,600 Amps Peak and 800 Amps continuous** during starts.

Series	DC Output Amperage
3000	2,600 cranking amps; 300 amps for pre-start operations
2000	2,500 cranking amps; 200 amps for pre-start operations
1000	2,400 cranking amps; 100 amps for pre-start operations

DC OUTPUT CABLE: 20' of 4/0 cable with 3 pin aircraft plug standard.

AC INPUT CABLE: 50' with customer providing plug for hangar. Works on Single or Three Phase.

PANEL METERS: DC-Volt Meter, DC-Amp Meter, and State of Charge Meter (total of 3 meters)

MOBILE UNIT: Unit is very easily be maneuvered by hand or tug. It comes standard with a minimum of 12" Pneumatic tires (2 rigid/2 swivel) and a simple kick stand brake that lifts the front with the tow handle when tow handle is raised in the upright position. Upgrade to 16" Pneumatic steerable (not caster) tires and tapered bearings available for \$950 and brake for 16" these tires available for \$549.

UNDERCARRIAGE: 12" Pneumatic tires with simple kickstand brake standard. Upgrade to 16" Pneumatic tires and tapered bearings available as mentioned in paragraph directly above.

SHIPPING DIMENSIONS: 42"L x 49"W x 54"H; 634-642-650 lbs.

TERMS: Payment in full prior to shipping (deposit with order acceptable).
Freight FOB origin (Wellston, OK USA). Lead time to be agreed upon when ordering. Price does not include shipping expenses (freight) and may change without notice, so please confirm when ordering.



BATESFIELD GPU
930335 S. Pilot Dr.
Wellston, OK 74881

Phone: 405-258-2600
sales@gasgpu.com
Fax: 405-258-3066
www.GasGPU.com

