

MONOCHEM

TECHNICAL
BULLETIN

CITRUS CLEAN SUPER®



Liquid and Non-Drip Graffiti Cleaner & Remover

MADE IN U.S.A.

PRODUCT DESCRIPTION:

ITEM NO. 9800 & 9860

CITRUS CLEAN SUPER is a concentrated, heavy duty, easy to use, water-dilutable graffiti remover that does not contain methanol, methylene chloride or other prohibited solvents.

BASIC USES:

For Commercial Use Only.

CITRUS CLEAN SUPER is used to remove and clean graffiti from surfaces that are protected with **PERMASHIELD PREMIUM Graffiti Control System** only.

It is safe to use on vinyl composition tiles, ceramic tiles, terrazzo and marble. Do not use on asphalt tile.

PREPARATION:

To ensure suitability and desired results, conduct a test on each surface type before application.

- Wear eye protection and gloves. Avoid skin contact.
- Protect the surrounding vegetation, foliage, painted surfaces and non-masonry related materials from the splashing of the remover residue. Maintain good ventilation when working indoors.

APPLICATION: 9800 LIQUID VERSION

- CITRUS CLEAN SUPER** may be applied by brush, roller or sprayer.
- Apply it directly on the graffiti markings and allow it to set for 2-3 minutes (do not exceed 5 minutes). Do not allow cleaner to dry on the surface because the graffiti may get embedded into the softened coating (**CITRUS CLEAN SUPER** temporarily softens the **PERMASHIELD PREMIUM**).
- With a nylon hard bristle brush or scour pad, scrub the cleaner into markings. Spray on more cleaning solution, as needed, to maintain a wet surface and to remove the dissolved markings. Continuous wet scrubbing will remove the graffiti. After the complete removal, rinse the cleaned area well with water to neutralize the cleaner.
- Do not rinse the surface with water until the graffiti is completely removed.
 - Do not allow graffiti runs to dry on the surface because they may get embedded into the softened coating.
- Textured surfaces and embedded stains may require a repeat application.
- DO NOT DILUTE.** Use **CITRUS CLEAN SUPER** as-is.
- Do not use solvents such as M.E.K. or lacquer thinners to remove graffiti.
- Protect the surrounding vegetation, foliage, painted surfaces, and non-masonry materials from the splashing of the cleaner residue. Maintain good ventilation when working indoors.

APPLICATION: 9860 NON-DRIP VERSION

Follow the same procedures as the liquid application except:

- When the graffiti has been completely removed, wipe all of the residue off with a rag and water. For very textured surfaces, pressure washing may be required to remove the residue. After the complete removal, rinse the cleaned area well with water to neutralize the cleaner.

COVERAGE:

100 to 200 square feet per gallon, depending on porosity and profile of the surface.

CAUTION:

- **COMBUSTIBLE.** Do not smoke when using **CITRUS CLEAN SUPER**.
- Keep out of reach of children.
- Harmful if swallowed.
- Can be absorbed through the skin. Avoid prolonged exposure with skin.
- Protect the eyes and skin by wearing protective eye wear, clothing and gloves. Wash items thoroughly after handling.

FIRST AID:

Refer to the **CITRUS CLEAN SUPER** MSDS for complete information.

Skin Contact: Wash with soap and water immediately.

Eye Contact: Flush with plenty of water for 15 minutes. Get medical attention.

Ingestion: Seek medical attention. If person is drowsy or unconscious, do not give anything by mouth; place person on the left side with head down. Contact medical personnel for advice about whether to induce vomiting.

Inhalation: Remove the affected person to fresh air. Give artificial air respiration if not breathing. Get immediate medical attention.

CAUTION!

CITRUS CLEAN SUPER (#9800) is formulated to remove graffiti from surfaces protected with **PERMASHIELD PREMIUM**.

CITRUS CLEAN (#9700) is designed to remove graffiti from surfaces protected with **PERMASHIELD SACRIFICIAL** and **PERMASHIELD NON-SACRIFICIAL**.

WARRANTY INFORMATION: MONOPOLE believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product or products. It is your responsibility to thoroughly test the product in your specific application to determine its safety and performance capabilities. Since use of this product is beyond our control, MONOPOLE, INC. cannot assume any risk or liability for results obtained when not used according to our specifications and directions. Unless MONOPOLE provides a specifically written statement of fitness for a particular use, MONOPOLE'S sole warranty is that the product will meet its current sales specifications. MONOPOLE disclaims any other expressed or implied warranties, including the warranty of merchantability and fitness for use. Your exclusive remedy and MONOPOLE'S sole liability for breach of warranty is limited to a refund of the purchase price or replacement of any product proven to be defective. In no event shall the seller be liable for any loss of profits or other consequential damages, including labor charges.

3

CONCRETE CLEANING 03910
SPECIALTY CHEMICALS

MONOPOLE INC.
UPDATED APRIL 2012



MONOPOLE INC.

Manufacturer of
U.S. SPECIALTY COATINGS

4661 Alger Street • Los Angeles, CA 90039

Tel: 818-500-8585 • Fax: 818-502-0818

www.monopoleinc.com • Email: info@monopoleinc.com