



# WARRIOR ROOFING MANUFACTURING

P. O. BOX 40185 • TUSCALOOSA, AL 35404 • PHONE (205) 553-1734 • FAX (205) 553-1755

323 DEVELOPMENT AVENUE • CHAMBERSBURG, PA 17201 • PHONE (717) 709-0323 • FAX (717) 709-0027

## SPECIFICATIONS

### # 30 ASTM

Our #30 ASTM asphalt saturated organic felt is manufactured to meet or exceed the following :

**ASTM – D226, Type II - Commonly called No. 30 Asphalt Felt**

**FED SPECIFICATION - HHR - 595B, TYPE 30**

**U.L. SPECIFICATION - U.L. STANDARD 55A FOR TYPE 30 ASPHALT SATURATED ORGANIC FELT**

Dimensions and specifications of No. 30 ASTM asphalt felt are :

<b>Width of roll :</b>	36" + or - .7%
<b>Area :</b>	216 sq. ft.
<b>Net mass of saturated felt :</b>	26.0 lbs./100 sq. ft.
<b>Net mass of saturant :</b>	15.0 lbs./100 sq. ft.
<b>Saturant Weight :</b>	Shall not be less than 1.5 times the weight of the moisture free felt.
<b>Saturant efficiency :</b>	Shall be no less than 70% for type 30 asphalt saturated felt.
<b>Packaging :</b>	The rolls are wrapped securely and the manufacturer's or distributor's name, type, and specification markings are evident on the label. UPC bar coding is included on all our labels.

**Important: Warrior Roofing Manufacturing is a statewide approved vendor for the State of Florida. The Florida Product Approval Code # is FL 2346. Per Florida Building Code 1517.4.1 this product is marked with a yellow line signifying compliance with High Velocity Hurricane Zone requirements.**