



ADHESIVE SOLVENT

FOR SPRAY SYSTEMS & EQUIPMENT

General Description

- A blend of acetone, toluene and light hydrotreated distillate that is designed to dissolve and remove dried adhesive film
- For detaching incorrectly bonded surfaces
- Cleans equipment such as brushes, roller covers, spray guns, pumps and pressure pots
- Not recommended for thinning adhesive products
- Professional use only
- Does NOT require stirring before use

Applications to Avoid

Do not use this product or any other to thin Wilsonart Adhesives

Availability

1-gallon cans, 5-gallon pails, 55-gallon drums

General Use Instructions

Use only after you have read and understand the warnings, safety measures and first aid instructions printed on container. Apply and allow to dry only in a well ventilated area. Application and drying must be in an approved spray booth or in an area provided with approved ventilation to exhaust the solvent vapors. Use outdoors when possible. If indoors, open all windows and doors, and shut off all sources of ignition.

For Equipment Cleaning

Use WA 110 to remove excess adhesive and to clean equipment immediately after use. Cleaning becomes more difficult as the adhesive sets longer. Brushes and rollers may be stored suspended in WA 110 between uses. Use WA 110 to clean application equipment, including pumps, spray guns or other equipment by circulating through the spray system.

For Adhesive Residue Removal

WA 110 may also be used to remove adhesive overspray or residue from finished products. Dab rag in solvent and lightly rub residue, increasing rubbing pressure as needed. Do not flood surfaces during cleaning as solvent will attack bonds and cause edges and seams to lift.

For Detaching Incorrectly Bonded Surfaces

To separate incorrectly bonded surfaces, apply WA 110 to the adhesive line. Keep the adhesive line wet with solvent while pulling the surfaces gently apart as the solvent loosens the bond until the pieces can be separated. Allow the two surfaces to dry THOROUGHLY before attempting to rebond using fresh adhesive. DO NOT TRAP SOLVENT IN THE NEW BOND.

Thinning

Even though WA 110 is a true adhesive solvent, thinning any Wilsonart adhesive with WA 110 is NOT recommended and may lead to bond problems.

Storage/Shelf Life

- Close container tightly when not in use.
- Rotate stock.
- Shelf life expires 2 years from manufacture date.
- Store in a cool, well ventilated area and away from ignition sources.

Primary Contents

Light hydrotreated distillate (CAS 68410979), Acetone (CAS 67641), Toluene (CAS 108883)

Physical Properties

Color:	Clear
Odor:	Strong Solvent
Density:	6.26 lbs/gallon
Solids Content:	0%
VOC/liter of material:	531 g/L (Calculated)
VOC(less water & exempt solvents):	735 g/L (Calculated)
VHAP Content:	182 g/L (1.52 lbs/gal)
Flashpoint:	-14.7°C/5.5°F (Closed Cup)
Composite part. pres.:	175 mm Hg @ 20°C
Nonphotochemically Reactive	

Shipping Information

- Ship Domestic Ground
- Flammable Liquids, N.O.S. (Contains toluene, acetone), Class 3, UN1993, PGII

Warranty

NO WARRANTY: WILSONART MAKES NO WARRANTIES, EXPRESS OR IMPLIED. NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. The person using the product (the "User") is solely responsible for determining whether the Wilsonart product is appropriate and/or suitable for User's purpose and method of application.

LIMITATION AND EXCLUSION OF REMEDIES AND DAMAGES: The exclusive and sole remedy, and Wilsonart's exclusive and sole obligation, for any defect of this Wilsonart product is the refund of the purchase price of the product. Wilsonart shall not, under any circumstances or under any legal theory, be liable to the Purchaser or any other person for special, incidental or consequential damages of any nature, including without limitation damages to, or loss of use of, property, damages for loss of profits or revenues or any other damages arising from the purchase or use of the product. Wilsonart's liability will in no event exceed the purchase price of the product.

Clean-up/Disposal

Dispose of waste solvent and solvent soaked rags in accordance with regulations. Empty container may contain hazardous residue or flammable vapors which may explode upon ignition. Do not allow in any sewers, on the ground or into any body of water. Contact local authorities for further guidance

Precautionary Information

Refer to product label and material safety data sheet for Health & Safety information before using this product.

Contact

Customer Service: 1-800-433-3222 or adhesives@wilsonart.com
Visit www.wilsonartadhesives.com for information