

# SILICONE LUBE WB

- Water Based Lubricant
- Mold Release Agent
- For Rubber and Plastic Parts Assembly
- Non-Toxic
- Nonflammable

## ■ PRODUCT DESCRIPTION

A multipurpose, water based silicone lubricant. Excellent for use as a rubber lubricant and as a mold release agent. Heavy silicone concentration provides maximum release capacity. Contains double the silicone content of leading aerosols for increased lubricity and protection.

## ■ DIRECTIONS

Product may be sprayed, brushed or squirted. Shake or stir well before using. Apply sparingly and evenly for best results.

## ■ RUBBER LUBRICANT

When used as a rubber lubricant, it provides a temporary, wet, slippery surface that makes assembly of plastic and rubber parts fast and easy. The product will then dry to a thin protective film or be absorbed into natural or synthetic rubber.

Seals/O-Rings	Channels	Bumpers
Boots	Glass Setting Strips	Shock Mountings
Wiring Harnesses	Wheels/Tires	Vibration Mountings

## ■ MOLD RELEASE AGENT

When used as mold release agent, the high silicone content provides maximum release capacity. For use on all metal, plastic and rubber castings. Heat stable to 500°F.

Acrylics	Celluloses	ABS Resins
Polystyrenes	Rubber	Melamines
Metals		

## ■ AVAILABILITY

PART#	SIZE (QTY/CS)
M-15841	1 Gal (4)
M-15845	5 Gal
M-15847	55 Gal

**Ashburn Chemical Technologies**

7403 Wright Rd.

Houston, Texas 77041

Ph: (832) 399-1000

Fax: (832) 399-1010

[www.ashburnchemical.com](http://www.ashburnchemical.com)