



# Heavy Duty Ultrasonic Cleaner Degreaser Concentrate

## Features & Benefits

- Deep Cleaning Formula
- Rapidly Removes Grease and Oil
- Removes Baked-On Carbon Deposits
- Does Not Emulsify Oil – Rejects Oil to the Surface
- Safe, Water-Based Formula
- Weldable and Paintable
- Improves Ultrasonic Cavitation Performance
- Contains Corrosion Inhibitors
- Produces Cleaner & Brighter Parts

## Removes:

- Heavy Viscosity Oils
- Greases
- Waxes
- Baked-On Carbon Deposits
- Oxidized and Gummy Deposits

## For:

- Metal Parts and Surfaces
- Industrial Equipment
- Machined Parts
- Engine Remanufacturing
- Transmission Remanufacturing

## PRODUCT DESCRIPTION

**ENVIROGREEN SUPERSONIC** is a powerful, heavy-duty cleaner and degreaser formulated to remove the most difficult soils including baked-on carbon deposits. Excellent for use in ultrasonic and immersion cleaning of ferrous and non-ferrous parts. Formulated to cut through any grease, dirt, oil, and grime and then suspend the soil. Surfaces will be residue free and can be welded or painted. Contains corrosion inhibitors to provide in-process rust protection.

## APPLICATIONS

### ULTRASONIC CLEANING:

Safe, non-flammable replacement for petroleum solvents.

Can be used on all ferrous and non-ferrous materials including aluminum.\*

Use to remove carbon deposits and degrease and clean

Remanufactured components ■ Engines ■ Transmissions  
Machined parts ■ Industrial parts

\* For aluminum, mix concentration must be at or below 10%. Material compatibility should always be confirmed.

### HEAVY DUTY DEGREASING:

Excellent degreaser for use in removing grease and oil from metal surfaces.

Removes petroleum based oils as well as animal fats and vegetable based oils.

Grease ■ Motor Oil ■ Lubricants ■ Carbon Deposits ■ Cutting Fluids  
Animal Fats ■ Vegetable Oils

Machine Shops ■ Industrial Plants ■ Commercial Facilities



# Heavy Duty Ultrasonic Cleaner Degreaser Concentrate

## TYPICAL ANALYSIS

BOILING RANGE: .....	212+
COLOR:.....	Clear, light Yellow
EVAPORATION RATE:.....	< 1
FLASH POINT: .....	N/A
FOAM STABILITY:.....	Low Foam
ODOR:.....	Mild
FREEZE/THAW: .....	3 Cycles
HARD WATER TOLERANCE:.....	Excellent
pH (concentrate):.....	13.5 - 14.0
RINSEABILITY: .....	Excellent
SHELF LIFE: .....	One Year +
SOLUBILITY:.....	100%
SPECIFIC GRAVITY:.....	1.2

## DIRECTIONS

**ULTRASONIC AND IMMERSION CLEANING:** Dilute product from 3% to 10% with water depending upon the soil conditions. Fill tank to level as recommended by the equipment manufacturer. Optimal temperature range: 130° F to 180° F

**HEAVY DUTY DEGREASING:** Dilute product from 3% to 10% with water depending upon the soil conditions. Spray, brush, or wipe solution onto surface to be cleaned. Wipe up solution with clean cloth or towel.

## AVAILABILITY

PART#	SIZE (QTY/CS)
M-02895	5 Gal
M-02897	55 Gal
M-02893	275 Gal



7403 Wright Rd. Houston, TX 77041  
 ph: 832.399.1000 fax: 832.399.1010  
[www.ashburnchemical.com](http://www.ashburnchemical.com)