

INMAR CORP.

With subcontracted services provided by:

C.D. PRODUCTS, INC.

EPOXY, URETHANE & FIBERGLASS FLOORING AND LINERS

918 N. UNION ST., APPLETON, WI 54911

(920)739-8685 FAX: (920)739-8704

E-Mail: cdpepoxy@aol.com

WWW.CONCRETEDEFENSE.COM

STATIC COEFFICIENT OF FRICTION OF VARIOUS SURFACES

TRACTIONITE	1.05	
SAFETY SURFACE	.95	
#1300 W/24 GRIT ALUMINUM OXIDE HEAVY SPRINKLE	.90	
PFAC III	.74	
SAND BROADCAST ONE FILL COAT	.72	
D'FOYR SLIP RESISTANT WAX	.70	
1300 W/30 GRIT ALUMINUM OXIDE ONE TOP COAT	.68	
#1110 W/36 GRIT ALUMINUM OXIDE ONE TOP COAT	.60	
3M QUARTZ BROADCAST ONE FILL COAT	.58	
RENU- GLAZE	.58	
#1110 W/3050 GRIT SILICA SAND HEAVY SPRINKLE	.56	
OLD SMOOTH CONCRETE	.56	
#4100 CLEAR EPOXY ONE YEAR IN FIELD	.55	
1300 LARGE/EX LARGE TXR AGENT	.55	
UNSEALED CONCRETE GARAGE FLOOR	.53	
#1300 W/ SMALL TEXTURE AGENT	.52	
BLACK UNWAXED VA TILE	.51	
SONNENBORNE CURE AND SEAL ON NEW CONCRETE	.50	
NEW SMOOTH CONCRETE	.50	
QUARTZ BROADCAST 2 FILL COATS AND ONE #2200 TOPCOAT	.44	
CERAMIC TILE 1' X 1' W/ SLIGHT TEXTURE	.42	
#2400 CLEAR W/ LARGE TEXTURE AGENT	.42	
#1300 CLEAR NEW	.40	
#1110 RED NEW	.40	
#2400 CLEAR W/SMALL TEXTURE AGENT	.39	
#1300 ESD	.38	
#2411 URETHANE	.37	
CERAMIC BATHROOM TILE 1"X 1"	.36	
SQUARE 9"X9' VA TILE	.34	
VINYL CHIP FLOOR NEW	.34	
#2200 ALIPHATIC URETHANE -CLEAR NEW	.32	
GLASS.		.32
470-300 1.25% WAX SURF-SMOOTH	.31	
#4100 - 100% SOLIDS EPOXY- NEW	.28	
FORMICA	.26	
1300 & 1121 TFE	.22	

NOTE: COF READINGS TAKEN ON DRY SURFACES. WATER OR GREASE WILL DECREASE COF

RANGES IN DIRECT PROPORTION TO THEIR AMOUNTS. JUNE 7, 2007